

COMPRESSED AIR | CHILLER & COOLING BEST PRACTICES

airbestpractices.com

coolingbestpractices.com

June 2021

System Assessments



FOOD & BEVERAGE PROCESSING
& PACKAGING MONTHLY FEATURE

26 **Brewing Energy Conservation at Molson Coors Canada**

6 **Corporate GHG-Reduction News**

20 **BEKO Technologies Remains Ahead of the Curve**

30 **Choosing a Cooling Tower – Crossflow or Counterflow?**

36 **Isentropic Efficiency of Rotary Screw Air Compressors**

The Atlas Copco logo is positioned in the top right corner of the page. It consists of the brand name "Atlas Copco" in a white, serif font, centered between two horizontal white bars. The background of the entire page is a photograph of an industrial facility with large grey metal cabinets, some of which are partially covered with blue protective sheeting. In the foreground, there are various pipes and mechanical components on a metal table. A large, semi-transparent blue triangle in the bottom right corner contains technical drawings and a large white question mark on the floor.

Ready for 100% Quality Air?

You've spent years developing the perfect product and we bet oil or microorganisms were not part of the plan. Without putting the right equipment and testing in place, potentially harmful microorganisms can thrive in your compressed air system and damage the integrity of your products and processes. That's why we've developed a two-fold solution. First, a range of audits based around air quality that can be performed on any system. Second, prevention always beats cure! Our multi-level product and service offering guarantees dry, oil-free air that's matched to your budget and efficiency goals.

It's not just about your compressor – it's about the entire compressed air system working together to keep your production safe. Peace-of-mind is only a call or click away.



866-472-1013



www.atlascopco.com/air-usa

QUALITY, SAFETY & RELIABILITY FEATURES

20 BEKO Technologies Remains Ahead of the Curve

By Mike Grennier, Compressed Air Best Practices® Magazine

30 Choosing a Cooling Tower for Your Application – Crossflow or Counterflow?

By Eric Rasmussen, SPX Cooling Technologies, Inc.



SUSTAINABILITY & ENERGY/WATER EFFICIENCY FEATURES

26 Brewing Energy Conservation at Molson Coors Canada

By Roderick Smith, Compressed Air Best Practices® Magazine

36 Isentropic Efficiency of Rotary Screw Air Compressors

By Brian Parks, Fourth Utility Consulting

SUSTAINABILITY & EFFICIENT TECHNOLOGY NEWS

6 Corporate GHG-Reduction News

Tate & Lyle, Colgate-Palmolive, Beiersdorf, Danone, Firmenich, Owens Corning, Electrolux, Carlsberg

44 Compressed Air Technology

46 Chiller & Cooling Technology



EVERY ISSUE

4 From the Editor

49 Advertiser Index

49 The Marketplace | Jobs and Technology

Compressed Air Best Practices® (USPS# 17130) is published monthly except January-February combined by Smith Onandia Communications LLC, 37 McMurray Rd., Suite 104, Pittsburgh, PA 15241. Periodicals postage paid at Pittsburgh, PA and additional mailing offices. POSTMASTER: Send address changes to: Compressed Air Best Practices®, 37 McMurray Rd, Suite 104, Pittsburgh, PA 15241.

Compressed Air Best Practices® is a trademark of Smith Onandia Communications, LLC. Publisher cannot be held liable for non-delivery due to circumstances beyond its control. No refunds. SUBSCRIPTIONS: Qualified reader subscriptions are accepted from compressed air professionals, plant managers, plant engineers, service and maintenance managers, operations managers, auditors, and energy engineers in manufacturing plants and engineering/consulting firms in the U.S. Contact Patricia Smith for subscription information at tel: 412-980-9902 or email: patricia@airbestpractices.com. REPRINTS: Reprints are available on a custom basis, contact Patricia Smith for a price quotation at Tel: 412-980-9902 or email: patricia@airbestpractices.com. All rights are reserved. The contents of this publication may not be reproduced in whole or in part without consent of Smith Onandia Communications LLC. Smith Onandia Communications LLC. does not assume and hereby disclaims any liability to any person for any loss or damage caused by errors or omissions in the material contained herein, regardless of whether such errors result from negligence, accident, or any other cause whatsoever. Printed in the U.S.A.

FROM THE EDITOR



Quality, Safety and Reliability

Since beginning my compressed air career in Spain in 1992, I've had the good fortune to work with BEKO Technologies products and people. Back then, the firm I worked for sold their innovative zero-air-loss condensate drains and we learned to educate plants on the cost of compressed air – sound familiar!? We are very pleased to have had the opportunity to interview their leadership, in the U.S. and Germany, and bring you an article where they express their visions of and investments in the future.

Our subscribers, working for engineering firms and manufacturing plants, have strongly encouraged us to integrate the compressed air and chiller/cooling best practices topics into one larger, higher-impact, technical journal. We are transitioning in this direction and are grateful for the continued support of SPX Cooling Technologies, Inc. – the firm behind the Marley brand of cooling towers. Their contribution this month is titled, “Choosing a Cooling Tower for Your Application - Crossflow or Counterflow?”

Productivity, Sustainability & Energy Conservation

The *monthly food & beverage industry feature article* is on the efforts underway to optimize compressed air at the Molson Coors brewery in Toronto, Canada. One of the largest in Canada, they brew 3.3 million hectoliters of beer per year – the equivalent of 980 million 12 oz. cans! I hope you enjoy my interview article with their team.

For “serious compressed air people and users” (is that a thing?), we bring you a very useful article titled, “Isentropic Efficiency of Rotary Screw Air Compressors,” written by Brian Parks. The Compressed Air & Gas Institute has introduced this important pressure-related factor into their rotary screw air compressor data sheets. This article will help readers understand why and what it means – it definitely helped me!

In closing, we are cautiously thrilled to see the COVID-19 metrics in our country head towards a direction where we hope officials can soon announce the safe and full reopening of the economy. Please keep our Chicago-area November 2-5, 2021 Expo & Conference in mind. We are pushing full steam ahead with our plans to make it happen and hope to see you there!

Thank you for investing your time and efforts into *Compressed Air and Chiller & Cooling Best Practices*.

ROD SMITH, Editor
tel: 412-980-9901
rod@airbestpractices.com

COMPRESSED AIR BEST PRACTICES® EDITORIAL ADVISORY BOARD			
Industrial Energy Managers	Doug Barndt	Energy Manager	Barndt Consulting
	John Bilsky	Facilities Maintenance	Gentex Corporation
	Bhaskar Dusi	Corporate Energy Manager	CEMEX USA
	Richard Feustel	Senior Energy Advisor	Leidos
	William Jerald	Energy Manager	CalPortland
	Michael Jones	Director Corporate Energy	Intertape Polymer Group
	Robert Kirts	GTS Energy Manager	Stanley Black & Decker
	Kurt Kniss	Energy/Reliability Engineer	Shaw Industries
	Leslie Marshall	Corporate Energy Engineer	General Mills
	Ethan O'Brien	Group Energy Manager	Klöckner Pentaplast
Compressed Air System Assessments	Brett Rasmussen	Senior Utilities Engineer	Nissan North America
	Brad Runda	Director Energy & Utilities	Purdue University
	David Andrews	Vice President, Global Marketing & Communications	Sullair
	Steve Briscoe	Director, Sales	Pattons
	Tilo Fruth	President	Beko USA
	Chris Gordon	President	Blackhawk Equipment
	Jan Hoetzel	General Manager	Airleader USA
	Paul Humphreys	Vice President Communications	Atlas Copco
	Phil Kruger	General Manager	Harris Equipment
	John Lucidi	Sales & Marketing Manager	Parker GSF Division
Wayne Perry	Sr. Technical Director	Kaeser	
Eric Solverson	Vice President	Total Equipment Company	
Derrick Taylor	Manager	PneuTech Products	
Jim Timmersman	Senior Auditor	Power Supply Industries	
Jeff Yarnall	Auditing Manager	Rogers Machinery	
Compressed Air & Gas Institute, Compressed Air Challenge			



2021 MEDIA PARTNERS






mikropor

Manufacturing Forward

Save up to *5% Power from the Feed Air Compressor



Engineered and integrated Pre/Post Filtration with greater media surface

* Every 2 PSI of Differential Pressure equals to 1% of Feed Air Compressor's Energy Consumption. Other Filters and Dryer configurations can have 8 to 12 PSID or more.

- ▶ Complete Air Treatment (less than 3 PSID differential - CAGI Verified)
- ▶ Engineered Pre/Post Filtration with greater media surface
- ▶ Highly Efficient, Ultra Low Pressure Differential Heat Exchanger
- ▶ Air Quality Class 1.4.1 as per ISO 8573



**MK-US & MCY-US
Air Treatment Packages**

Please contact us for a Complimentary Consultation
support@mikroporamerica.com



CORPORATE GHG-REDUCTION NEWS*

* Scope 1 and 2 GHG Emissions from Direct Operations

Tate & Lyle Exceeds 2020 Environmental Targets

Tate & Lyle PLC (Tate & Lyle), a leading global food and beverage ingredient supplier, announced in April 2021, that it has exceeded its 2020 environmental targets, set using a 2008 baseline. Scope 1 and 2 greenhouse gas (GHG) emissions, generated by on-site energy use, were reduced by 25% (target of 19%), and waste to landfill was reduced by 37% (target of 30%). These environmental benefits are equivalent to the carbon captured by nearly 1 million acres of US forestry and 1,700 fewer garbage trucks taken to landfill.

Tate & Lyle's 2020 targets were a 19% intensity reduction in Scope 1 & 2 greenhouse gas emissions and a 30% intensity reduction of landfilled waste, both from a 2008 baseline.

The GHG emissions reduction target was delivered largely by investing in the transition to cleaner energy sources, such as replacing the coal boiler with a natural gas-fired combined heat and power system at the corn wet mill in Loudon, Tennessee (pictured). The waste

target was met largely by eliminating certain waste streams from the production process by reclaiming organic solids which would otherwise have been sent to landfill.

In May 2020, Tate & Lyle set new ambitious environmental targets for 2030 for GHG emissions, waste, water and sustainable agriculture. The 2030 GHG emissions reduction targets have been validated as science-based by the Science Based Targets Initiative, meaning they are in line with the goals of the Paris Agreement in Climate Change.

Nick Hampton, Chief Executive at Tate & Lyle, said: "We are proud of the progress we have made against our environmental commitments over the last decade, and are now absolutely focused on delivering our new targets for 2030. Every part of our global team, from production to procurement, supply chain to sales, are playing their part to deliver our purpose of Improving Lives for Generations by caring for our planet and helping to tackle the world's biggest shared challenge of climate change."

Sara Leeman, Global Environmental Leader at Tate & Lyle, said: "In setting our 2030 environmental commitments, we broadened our scope to include water reduction, the beneficial use of all our waste, emissions resulting from our value chain (Scope 3), and support for sustainable agriculture. Our new targets mean we are really challenging ourselves to make real and lasting improvements to the environment around us, while also continuing to grow our business."

Tate & Lyle's 2030 environmental targets, announced in May 2020, are as follows:

- ✦ By 2030, we'll have delivered a 30% absolute reduction in our Scope 1 and 2 greenhouse gas emissions with an ambition to reach a 20% reduction by 2025.
- ✦ By 2030, we'll have delivered a 15% absolute reduction in our Scope 3 greenhouse gas emissions.
- ✦ By 2025, we'll have eliminated coal from all our operations.
- ✦ By 2030, 100% of our waste will be beneficially used with an ambition to reach 75% by 2025.
- ✦ By 2030, we'll have reduced water use by 15%.
- ✦ We'll maintain sustainable acreage equivalent to the volume of corn we buy globally each year, currently 1.5 million acres, and through partnerships we'll accelerate the adoption of conservation practices.



Tate & Lyle operates the only two U.S. EPA Energy Star accredited corn wet mills in the U.S. including its facility in Loudon, Tennessee.

Find out more at <https://www.tateandlyle.com/purpose/caring-for-our-planet>

Tired of downtime and scrap as a result of poor compressed air quality?

Moisture is found in compressed air lines and exhausting from valves and actuators on equipment thereby reducing component life and machine efficiency. Tired of draining water and oil from your compressed air lines every spring? Tired of cleaning or replacing pneumatic components well before their lifespan?



The Solution: Remove the Moisture




SMC Dryers provide low energy consumption and efficient operation in sizes to work with air compressors from 1/3 to 100 horsepower (0.24kW to 75kW) and flow ranges from 10 scfm to 400 scfm.

The SMC Dryer Advantage:

Environmentally friendly R134a/R407C Refrigerant

Simple Control System, incorporating easy to read evaporator gauge

Stainless Steel Heat Exchanger providing long-life and low-pressure drops



SMC Corporation of America
10100 SMC Blvd., Noblesville, IN 46060

(800) SMC.SMC1 (762-7621)

www.smcusa.com
e-mail: **sales@smcusa.com**
International inquiries:
www.smcworld.com

Corporate GHG-Reduction News

Beiersdorf Group Sets Ambitious Climate Targets for 2025

Beiersdorf Group, in June 2020, publicly committed to new, ambitious climate targets, thus contributing to limiting global warming to 1.5°C. The entire Group plans a significant reduction across the full spectrum of its CO₂ emissions by 2025, which applies equally to both its Consumer and tesa Business Segments. Energy-related emissions (Scopes 1 and 2) are to be reduced by 30 percent in absolute terms by 2025. In addition, a clear cut is also planned in Group-external CO₂ emissions (Scope 3), by suppliers and service providers, for example: The Group has set a value chain GHG emissions-reduction target of 10 percent by 2025.

These ambitious climate targets have now been officially endorsed by the “Science Based Targets initiative” (SBTi), meaning this organization confirms that Beiersdorf’s targets are aligned with independent global climate scientists’ latest findings. To date, 111 companies worldwide have set themselves targets that received SBTi approval. Currently only eight companies headquartered in Germany are among these, with just a further eight around the world from the “Consumer Products & Durables” sector.

“Climate change confronts us as a society with tremendous challenges. We are taking action based on our sense of duty and our unshakeable belief that we must commit fully and immediately to climate protection, to counteract global warming and its severe consequences,” explains Stefan De Loecker, Chairman of the Beiersdorf AG Executive Board. “The official endorsement by the SBTi of our new, ambitious climate targets is welcome confirmation that we are on the right

track to actively co-shape a sustainable future for our global society.”

In addition to the SBTi’s endorsement of climate targets for the entire Beiersdorf Group, the Consumer Business Segment has set itself the target of a 30 percent absolute reduction in its Scope 3 emissions by 2025. On top of this, all Consumer Business Segment production sites are to become climate-neutral by 2030.

Beiersdorf, and in particular its Consumer Business

Segment, has made major progress in recent years in reducing its CO₂ emissions: The Group successfully cut its energy-related CO₂ emissions by 60 percent in absolute terms between 2014 and 2019. Various energy-saving measures, the LEED seal-winning sustainable design of production and office locations, and the transformation to green logistics are just a few examples of the Beiersdorf Group’s uncompromising climate protection program. Since the end of 2019, 100 percent of the electricity purchased worldwide comes from renewable energy sources.

In its CARE BEYOND SKIN sustainability agenda, launched at the beginning of 2020, Beiersdorf is bundling its climate commitment and action measures in the focus area “For a Carbon Positive Future”. Alongside the central issue of climate change, this sustainability agenda defines a further six focus areas in which the Group’s Consumer Business Segment, comprising the well-known brands NIVEA and Eucerin, is committed to making a meaningful and measurable contribution to the environment and society.

Also the tesa Business Segment has been implementing numerous measures to increase

energy efficiency and reduce CO₂ emissions in the past years. For example, specific CO₂ emissions per ton of end product have been reduced by 34.5 percent since 2015, saving almost 60,000 tons of CO₂ per year. At present, 27 percent of electricity is used from renewable sources and 38 percent is produced by combined heat and power generation (CHP).

On February 16, 2021, Beiersdorf announced it further stepped up its efforts in sustainability in the reporting year with the “Care Beyond Skin” sustainability agenda. In the current ranking of the NGO “Carbon Disclosure Project”, Beiersdorf has been listed as a “Climate A List Company” for its environmental transparency and ambitious targets on climate action. Both business segments – Consumer and tesa – now meet 100% of their electricity needs from renewable sources. In 2020, Consumer switched to recycled materials for 90% of all its PET bottles in Europe. It also met the target of using 100% sustainably certified palm oil in all cosmetics manufacturing.

More information on Beiersdorf’s Consumer Business Segment sustainability commitment and progress is available at: www.beiersdorf.com/sustainability. For more information about the tesa Business Segment, please visit: <https://www.tesa.com/en/about-tesa/responsibility>.



Jean-Francois Pascal, Vice President Corporate Sustainability, Beiersdorf





Who is Quincy Compressor?

We are people passionate about engineering the most efficient and reliable air systems on the market.

Dedicated to endlessly serving our customer's needs and exceeding their expectations. We believe the best way to serve our customers is by offering our impartial knowledge. We will even recommend our competitor if we genuinely believe it is the best solution for you.

You can Count on Quincy.

QuincyCompressor.com



Corporate GHG-Reduction News

Danone recognized as global environmental leader with triple “A” score given by CDP

Danone announced, in December 2020, that it has been highlighted for the second year in a row as a world environmental leader by the international non-profit organization CDP, whose disclosure and scoring system is recognized as the gold standard of corporate environmental transparency.

Out of the 5,800+ companies scored in 2020, **Danone is one of the only 10 companies that achieved a place on the A List for the three environmental areas** covered by CDP of climate change, forests preservation and water security.

Since its first voluntary environmental disclose to CDP in 2010, Danone has gradually increased its score to reach the Triple “A” list last year for the first time. Being included this year again in these three prestigious lists is a great recognition of Danone’s ambitious and longstanding actions to build a low carbon economy, protect natural resources and increase its brands’ transparency.

Henri Bruxelles, Chief Operating Officer End-to-End Design-to-Delivery, declared: “For the second year in a row, Danone is recognized as a ‘Triple A company’ by the CDP. This is an important milestone and achievement that confirms how our ‘One Planet. One Health’ frame of action and our strategy to focus on grounded and local impact have turned into a deep transformation agenda with major steps taken by our business and brands in 2020: evian and Volvic became carbon neutral from the source to the consumers; the US organic milk leader Horizon Organic set the ambition to become carbon positive in 5 years; Karicare also embarked in a neutrality journey. We launched ‘We Act for Water’ movement, a set of urgent actions to foster the protection and access to water resources. And we created the first ever segregated Palm-Oil supply chain in the U.S. as part as our commitment to eliminate deforestation. I would like to thank all our teams for their dedication and passion in transforming our value chain, inventing a low carbon economy and protecting natural resources. Transparency is crucial to reinforce consumers’ trust in our brands and to provide the financial community with the right tools to assess the resilience and impact of our business models”.

The full methodology and criteria for the A List is available on CDP’s website at: <https://www.cdp.net/en/companies/companies-scores>.

Danone’s recent natural resources protection and climate achievements and ambitions:

- evian and volvic carbon neutral certification from source to consumer
- Wexford’s baby-formula facility carbon neutral certification (which produces leading brands like *Aptamil*, *Cow & Gate* and *Nutrilon* for consumers in 41 countries around the world).
- Karicare announcement to become the first milk formula brand in Australia and New Zealand to achieve carbon neutrality by 2030.
- Horizon Organic ambition to become Carbon Positive by 2025.
- Reach its full scope carbon emissions peak in 2019, five years ahead of its original plan and commitment and one year prior to the 1.5°C Science-Based Targets commitment. Going forward, its GHG emissions in absolute levels are set to decrease.
- Creation alongside two traders of the first ever Segregated Palm-Oil supply Chain in the U.S. as part of its commitment to eliminating deforestation.
- Publication of its Water Policy in order to act to preserve and restore water resources, today and for future generations
- Launch of “*WeActForWater*” by Danone Water brands, a set of urgent actions, ambitious objectives, and new investments, deployed by Danone’s iconic water brands, including evian,

Volvic, AQUA and Bonafont, it focuses on responsible packaging, climate neutrality, watershed preservation and access to safe drinking water.

For more information visit Danone at <https://www.danone.com>



GOIN' MOBILE

GA800 AC DRIVE FOR INDUSTRIAL APPLICATIONS

Already use your smartphone or tablet to interact with your television, your thermostat or your garage door opener? Would you love to do this with your variable speed drive?

Enjoy a beautiful and intuitive experience with the new Yaskawa GA800 featuring DriveWizard® Mobile.

Your days are complicated enough. Let us help simplify them.
Call Yaskawa today at 1-800-927-5292.



GO MOBILE TODAY:
<https://www.yaskawa.com/ga800-drive>



IT'S PERSONAL

YASKAWA



Yaskawa America, Inc. 1-800-YASKAWA
Email: info@yaskawa.com | yaskawa.com

Corporate GHG-Reduction News

Colgate-Palmolive Earns 11th Consecutive ENERGY STAR® Partner of the Year Award

In recognition of its commitment to 100% renewable electricity and to reducing its carbon footprint, Colgate-Palmolive Company announced (April 13, 2021) it has received a 2021 ENERGY STAR® Partner of the Year Award for Sustained Excellence for its leadership in energy efficiency across global operations. This marks the 11th consecutive year that Colgate has been recognized by the U.S. Environmental Protection Agency and the U.S. Department of Energy as an authority in energy-saving practices.

This honor recognizes Colgate's commitment to global sustainability, which is further defined in its 2025 Sustainability & Social Impact Strategy.

Over the past year, Colgate has achieved measurable progress towards meeting the ambitious sustainability goals outlined in this Strategy, including:

- Developing Colgate's first Renewable Energy Master Plan, which was prompted by two new targets: To source 100% renewable electricity for global operations by 2030 and to become net zero carbon in operations by 2040.
- Implementing 49 new capital energy projects around the world estimated to reduce Colgate's carbon footprint by nearly 9.2 million kilograms – equivalent to 1,000 homes' energy use for one year.

- Working with Colgate's largest suppliers to help increase their climate and energy awareness, with 35% of suppliers responding to our CDP Supply Chain request indicating they now have energy reduction goals.
- Continuing to hold "Energy Treasure Hunts" to encourage employees to uncover causes of energy waste and find opportunities for improvement. Since 2012, this program has identified nearly 2,400 energy savings projects with the potential to reduce Colgate's energy consumption by about 400,000 MWh and CO₂ emissions by more than 140,000 metric tons – equivalent to the carbon sequestered by over 2 million trees grown for 10 years.

SUPER-PAK Series
Large Compressed Air Systems

- Designed for 4,000 – 10,000 CFM applications
- Ships from factory pre-plumbed, primed and leak tested
- Three layers of redundancy
- System functions on ALL compressor lubricants
- No exposure to mold, bacteria or E. coli
- No maintenance required

MICRO IDC SMART-PAK **SUPER-PAK**

CLEAN RESOURCES
Condensate Management—Engineered for Life

1540 Louis Bork Dr. Batavia, IL 60510 • 800-566-0402 • Sales@cleanresources.com

EPA COMPLIANCE GUARANTEED
100%
10 PPM OR LESS GUARANTEED FOR LIFE OF UNIT

The honor from ENERGY STAR® also recognized Colgate's progress towards its long-time goal of reducing Scope 3 emissions by educating consumers about how to save water while using their products. Colgate's Save Water campaign has helped consumers avoid more than an estimated 8.3 million metric tons of CO₂ and 155 billion gallons of water since 2016 (that's the amount of water it takes to fill 234,000 Olympic-sized pools).

"Since the Colgate brand is in more homes than any other, we have the opportunity to help people build sustainable habits into their everyday lives," said Ann Tracy, Colgate's Chief Sustainability Officer. "We are honored to be recognized by ENERGY STAR® for Colgate's achievements in sustainability and ongoing efforts to lead action on climate change – from encouraging suppliers to reduce their energy consumption to making our operations even more energy efficient to helping consumers lead more sustainable lives through the use of our products."

The 2021 ENERGY STAR recognition demonstrates Colgate's ongoing momentum in its mission to reimagine a healthier, more sustainable future for all people, their pets and our planet. As of 2020, Colgate certified its 20th TRUE Zero Waste plant – more than any other company in the world, was named the top performing Household Products company on the Dow Jones Sustainability Indices, and committed to furthering climate progress through participation in the UN Global Compact's Water Resilience Coalition. Additional details about Colgate's energy management and investment practices can be found in the Sustainability section of Colgate's website. For ongoing updates regarding Colgate's sustainability progress and accomplishments, follow Colgate on LinkedIn.

More background information about ENERGY STAR can be found at: energystar.gov/about and https://www.energystar.gov/about/origins_mission/energy_star_numbers.

For more information about Colgate's global business and how the Company is building a future to smile about, visit www.colgatepalmolive.com.


Firmenich Achieves 4th Consecutive CDP Triple "A" Recognition

Firmenich, the world's largest privately owned fragrance and taste company, announced in February 2021, it has ranked on the CDP Supplier Engagement Leaderboard 2020, setting the pace in environmental leadership. The leaderboard highlights the top 7% of companies that engage with their global supply chains on climate reporting and managing carbon emissions via CDP. This is Firmenich's fourth recognition from the gold standard in corporate environmental reporting this year, adding to the Group's third consecutive CDP Triple "A" score in climate, water, and forests management.



THE ROUND-THE-CLOCK,
TOUGH-AS-NAILS,
TRUST-IT-WITH-YOUR-LIFE,
MORE-UP-TIME, MORE-RUN-TIME,
TIME-AFTER-TIME
AIR COMPRESSOR

THAT'S THE TRUE MEANING OF RELIABILITY



EXPLORE THE BROAD RANGE OF NEW SULLAIR COMPRESSORS AT SULLAIR.COM

 **SULLAIR**[®]

A Hitachi Group Company

© 2020 Sullair, LLC. All rights reserved. SULLAIR.COM   

Corporate GHG-Reduction News

Firmenich Recognition (continued from page 13).

“It is a great honor to be one of only ten companies in the world to be ranked by CDP on its Supplier Engagement Leaderboard and to achieve triple “A” status for climate change, water security, and forests,” said Gilbert Ghostine, CEO Firmenich. “This fourth top score marks world-class recognition of our environmental performance and illustrates how Firmenich’s sustainability leadership is well entrenched within our company and beyond, with a positive impact on our supply chain.”

“Companies’ emissions don’t end at the factory door. CDP data shows a company’s supply chain emissions are, on average, over 11.4 times greater than its direct emissions. Meaningful corporate climate action means engaging with suppliers to reduce emissions across the value chain,” said Sonya Bhonsle, Global Head of Value Chains, CDP.



“We congratulate Firmenich for making it on to the CDP Supplier Engagement Leaderboard. This demonstrates that they are setting the pace in environmental management and their commitment to reduce emissions and lower environmental risks across their supply chain.”

“We were the first perfume and taste company to engage with our suppliers through CDP when we started disclosing our environmental performance more than 10 years ago,” said Neil McFarlane, Senior VP Quality, Health, Safety, Security & Environment, Firmenich. “As we power towards carbon neutrality in our direct operations by 2025, we are very proud of this achievement highlighting the incredible work done by our environmental and procurement teams, and hope it will inspire other companies to develop their own path towards zero impact.”

BEST PRACTICES

2021 EXPO NOVEMBER 2-4 CHICAGO, IL

COMPRESSED AIR / VACUUM / COOLING

OPTIMIZE ON-SITE UTILITIES

Powering Automation

Assure Product Quality & Safety

What can you do to reduce product rejects, mitigate the risk of contamination, minimize downtime, and decrease maintenance expenses? Attend **Best Practices EXPO & Conference** and learn how to prevent impurities from coming into direct or indirect contact with your product, treat your water to prevent legionella, ensure the safety of your pneumatic systems, verify oil free compressed air, and protect your food, pharmaceutical, paint, and medical device manufacturing processes, and more.

Register today for FREE EXPO admission and conference savings! cabpexpo.com

Sponsored by

This is the Group's third consecutive listing on CDP's annual Supplier Engagement Leaderboard. CDP assessed more than 5,000 companies on their supply chain engagement strategies, with almost 400 (7%) companies earning a place on the Leaderboard. Discover the business case for supply chain action and how it improves competitiveness and resilience in CDP's *Transparency to Transformation: A Chain Reaction*.

Learn more about Firmenich's ambitious 2025 and 2030 ESG targets at https://www.firmenich.com/company/sustainability/strategy/esg_ambitions_2030.

The Group's 2020 environmental initiatives and performance are detailed in its *Performance and Sustainability Report 2020*.

Carlsberg Opens Water Recycling Plant Becoming World's Most Water Efficient Brewery

On May 6, 2021, Carlsberg is inaugurating a new, revolutionary water recycling plant that recycles 90% of the process water at the Carlsberg brewery in Fredericia, Denmark. This makes the Fredericia brewery the most water efficient in the world. Learnings from the brewery will enable the group to reach its target to virtually eliminate water waste globally by 2030.

With the new water recycling plant, the Fredericia brewery will save more than 500 million liters of water a year. 90 percent of process water from the production of beer and soft drinks will be recycled in the production facility. Water consumption will be halved from the



hertz

KOMPRESSOREN

CLEAN, OIL-FREE COMPRESSED AIR ISO 8573-1 CLASS-0



hertz-kompressoren.us

Corporate GHG-Reduction News

current 2.9 hl of water per hl of beer to 1.4 hl of water per hl of beer.

“We are immensely proud to be able to unveil the world’s most water efficient brewing facility. Water is a basic ingredient in all our products, so water resource management is a high priority. Our water to beer ratio has always been low. Now we are taking it a step further. By recycling process water in our production, we are virtually eliminating water waste,” says Philip Hodges, EVP Integrated Supply Chain, Carlsberg Group.

Water is not only a basic ingredient in the products from Carlsberg but is also essential to the sustainability of the societies where the brewery operates, and clean water is a priority

in the UN Sustainable Development Goals. Therefore, Carlsberg has a goal of eliminating water waste by 2030 as part of the group’s sustainability program Together Towards Zero.

“We have a goal of zero water waste globally in 2030. As a global company, we have a responsibility to support the UN Sustainable Development Goals, and as a brewery, we have a special responsibility to reduce water waste in our global production. The new water recycling plant in Fredericia will generate important learnings that can be implemented across our breweries in the rest of the world,” says Carlsberg Group CEO, Cees ’t Hart.

It is estimated that the water recycling plant will also reduce the brewery’s energy

consumption by 10% through own biogas production and recirculation of hot water, further contributing to the Together Towards ZERO sustainability program.

The new plant is a result of broad collaboration in the *Danish partnership for Resource and water efficient Industrial food Production (DRIP)*. For the project to succeed both businesses, technical experts and health and food authorities have had to rethink how we use and reuse water and expand the limits of water purification and circularity.

“The plant in Fredericia is built on a new and innovative approach to cleaning and recycling process water where you, among other things, use UV-light to eliminate bacteria. At the

Worried About Moisture & Oil Contamination in Food Production?

Learn Quality & Safety Best Practices - View Our **FREE* On-Demand Webinars**

Our Extensive Library of Webinars Includes These Titles

- Safety and Quality in Compressed Air: Why You Should Care
- Safe Quality Food Standard: 5 Compressed Air Criteria
- Integrating ISO 8573-1 Compressed Air Quality Classes into SQF Food Safety Certification
- Global Food Safety Initiative (GFSI) Compliance: Two Compressed Air System Specifications

*Included with your free magazine subscription



Get FREE Instant Access* at airbestpractices.com/magazine/webinars

same time biogas is produced as a residual product, which can be used to produce energy. It is a whole new form of circularity in food production. In fact, the process water ends up being clean enough to drink, but we are only using the water to clean the production facilities,” says Carlsberg Denmark Brewing Director, Anders Kokholm.

The new facility will be inaugurated at a special event attended by the Danish Prime Minister as well as representatives from Carlsberg and the DRIP-partnership.

About Together Towards Zero

Together Towards ZERO is Carlsberg’s vision for a better and more sustainable future in a time with serious challenge such as climate change and water scarcity. The program consists of four goals: ZERO CO₂-emissions, ZERO water waste, ZERO irresponsible drinking culture and ZERO work-related accidents. Each of the four ambitions is supported by individual and measurable goals, which are to be obtained by 2022 or 2030.

Our business depends on the availability of clean water. No water, no beer. But the supplies are becoming more and more scarce in some regions where our beer is brewed, so we must use it sparingly.

With a goal to reduce water consumption in our breweries by half by 2030 and reduce it by 25 percent by 2022, we are obligated to eliminate water waste. Through community partnerships we help preserve common sources of water around our breweries with a focus on areas that are classified as high risk.

Read more about Together Towards Zero at <https://www.carlsberggroup.com/sustainability/our-ambitions/>

Vanessa Butani Appointed New VP Group Sustainability at Electrolux

Effective May 1, 2021, Vanessa Butani, current Head of Sustainability for Business Area Europe, will take on the role as VP Group Sustainability at Electrolux. She will replace Henrik Sundström, who is retiring from the company.

Vanessa Butani will lead Electrolux forward in the company’s For the Better 2030 framework, which covers the full value chain, from operations and products to helping consumers live more sustainably while using Electrolux products.

“This is an extraordinary opportunity to work across the entire organization to drive our sustainability agenda,” says Vanessa Butani.



Vanessa Butani, VP Group Sustainability, Electrolux

CLASS 0 CLASS ZERO OIL-FREE

Protect your valuable equipment with oil-less scroll and piston air compressors from ANEST IWATA. Quiet, reliable, energy efficient & Class Zero Oil-Free.

ANEST IWATA

www.anestiwata.com
Toll free: 800-440-0282

Interested in becoming a distributor?

FREE SUBSCRIPTION

DIGITAL EDITION FREE WORLDWIDE
PRINT EDITION FREE TO U.S. SUBSCRIBERS



EVERY ISSUE CONTAINS
BEST PRACTICES FOR

Cooling Towers

Central Plant Chillers

Cooling System
Components

Subscribe Now!



Subscribe at
coolingbestpractices.com

Corporate GHG-Reduction News

“We have ambitious but achievable objectives and I look forward to the journey ahead to drive positive change both at Electrolux and in the daily lives of our consumers.”

In her role, Vanessa Butani will become a member of the Electrolux Consumer Experience Leadership Team and report to Ola Nilsson, Chief Experience Officer at Electrolux.

“I’m very pleased to have Vanessa joining the team,” says Ola Nilsson. “She will play a key role in taking Electrolux sustainability agenda to the next level, and ensure we have a strong voice as a corporate sustainability leader as well as connect our sustainability conviction with the consumer.”

Vanessa Butani has a strong track record in the sustainability field. During an earlier eight-year period at Electrolux, she held several managerial roles in sustainability and connectivity. After three years outside Electrolux she re-joined the company to lead sustainability for Business Area Europe in January this year. She is replacing the current VP Group Sustainability, Henrik Sundström, who will be retiring after 36 years with Electrolux.

“Henrik has been instrumental in establishing Electrolux as a global leader in sustainability. We would not be where we are today without his foundational work in multiple roles across the company. I have no doubt that he will continue to stir impactful discussion with his knowledge and insights going forward,” says Ola Nilsson.

The search for Vanessa Butani’s successor as Head of Sustainability for Business Area Europe will begin shortly.

Visit <https://www.electroluxgroup.com/en/category/sustainability/>

Owens Corning Publishes 15th Annual Sustainability Report

Owens Corning (NYSE: OC) published, on April 1st, 2021, its 2020 Sustainability Report. The company’s 15th annual report, titled “Beyond Today, Shaping Tomorrow,” presents the results of the company’s sustainability work in the decade since 2010, as well as progress toward its ambitious slate of 2030 goals.

“Owens Corning faced unprecedented challenges in 2020, but remained committed to our broad sustainability agenda,” Chairman and Chief Executive Officer Brian Chambers said. “This report highlights the amazing accomplishments of our 19,000 employees who work hard every day to meet the needs of today while making the world a better place for the future. We’ve come a long way since we set our second set of long-term goals in 2010, and we have a clear vision of the work that lies ahead.”

In the report, the company’s sustainability results and commitments are presented through 16 topics that reflect stakeholders’ priorities. The topics span every aspect of sustainability, including product innovation, environmental footprint reduction, and the company’s impact on people and communities.

Frank O’Brien-Bernini, Senior Vice President and Chief Sustainability Officer said, “The most critical competence of sustainability talent, all across our company, is the ability to lead change. Every individual can shape the future. Our goals for 2030 and beyond, grounded in what the world needs us to get done, compel us to collaborate to accelerate progress.”

This year’s Sustainability Report includes:

- Results covering the 10-year goal period that concluded in 2020, with commentary from company leaders.

- Disclosures in response to the GRI Comprehensive standard, the Advanced UN Global Compact, the Task Force on Climate-related Financial Disclosures (TCFD) and the Sustainability Accounting Standards Board (SASB) reporting requirements.
- Information about product innovations for sustainability and the company's work to drive transformation for a circular economy and a decarbonized future.
- Discussion of the impact of COVID-19 on Owens Corning's employees and work around the world, as well as the company's response.

- An overview of the company's inclusion and diversity commitment and initiatives, including details about how the company is working to address racial equity and social justice issues.
- A new feature, "Speaking of Sustainability," in which members of the Owens Corning team discuss their work and their personal interest in sustainability-related topics.



#1 on the annual 100 Best Corporate Citizens list from 3BL Media for the second consecutive year. In addition, Owens Corporate was included on the CDP A List for both climate and water, and earned a spot on the Dow Jones Sustainability World Index for the 11th consecutive year (as industry leader for the Building Products Group for the eighth straight year).

Access the 2020 Sustainability Report and learn more about sustainability at Owens Corning at: <https://www.owenscorning.com/corporate/sustainability>.

In the past year, the company has earned top rankings and high scores from several external organizations, including ranking



Sullivan-Palatek Distributors Bring Value to Customers

Compressed air systems can be complex; that's why our Distributor network is key to providing end-users with the best compressed air solution for their businesses.

Advantages of purchasing a Sullivan-Palatek air compressor through our Distributors:

- » Appropriate product selection recommendations, including sizing and feature specification
- » Integration of all components of your compressed air system
- » Operating parameters adjustments, including pressure and modulation
- » Installation and electrical connection solutions
- » After-the-sale customer service and technical support

To connect with your local Distributor, start here
<https://www.sullivan-palatek.com/contact-sales-directors/>

To read about how our Distributors can benefit you
<https://www.sullivan-palatek.com/posts/SPI-Distributor-Advantage/>



Dependable by design.™

© 2021 Sullivan-Palatek, Inc.



BEKO Technologies Remains Ahead of the Curve

By Mike Grennier, Compressed Air Best Practices® Magazine

DRYPOINT® X desiccant dryers ready for shipment at the BEKO Technologies plant in Atlanta, Georgia.



Norbert Strack and Yannick Koch, Co-Managing Directors, BEKO Technologies (left to right).

► When a company serving the compressed air industry bundles a value-based approach with a commitment to developing technologies used to improve safety, save costs and protect the environment it can only mean one thing: Success.

Such is the case with BEKO Technologies GmbH, headquartered in Neuss, Germany. Started decades ago in a backyard garage in Düsseldorf, Germany, the independent, family-owned business has since grown to become a global leader in innovative technologies and complete systems for the treatment and management of compressed air and compressed gas.

Strong growth is also projected for the future, said Yannick Koch, Co-Managing Director,

BEKO Technologies, especially given the company’s strategic focus and its history of being ahead of the curve.

“Quality, efficiency and safety are what really counts in the end for users of compressed air. Those are their main goals” said Koch. “Our vision is to help them achieve those goals and do it in way that allows all of us to treat the environment more gently.”

Continuity in Leadership

Berthold Koch founded BEKO Technologies (<https://www.beko-technologies.com/en/en/>) in 1982 and led the company until he unexpectedly passed in 2007. Yet the company’s long tradition of a well-run family business continues. Yannick Koch, Berthold’s

eldest son, was named Co-Managing Director of the company earlier this year. The change in leadership also included the naming of Norbert Strack as Co-Manager. Former Managing Director Manfred Lehner retired at the end of 2020 after 30 years with the company.

Koch assumes responsibility for BEKO Technologies Sales, Service, Product Management, Marketing and Human Resources. Since 2015, he has served as the company’s Head of Global Corporate Development. Before joining BEKO Technologies, Koch was involved in various digitalization projects with an international industrial company. He is also an active shareholder in BEKO Holding where he helps shape socially relevant issues.

Strack, who joined BEKO Technologies in 2016 after serving in a variety of leadership roles at various industrial companies, assumes Finance and IT responsibilities, which is in addition to his responsibilities of Research and Development, Production, Supply Chain and Quality.

The newly named leaders plan to continue to foster BEKO Technologies’ culture of making long-term investments in compressed air technologies built around customers’ needs and industry trends.

“The market continues to gradually shift from being focused only on compressed air as a utility and volume to where it’s more about quality and efficiency, as well as sustainability.

Flowmeters for Compressed-Air Management

Economical

Install in minutes

Hot tap option

Wireless output available



cdimeters

3R Green Street · Woburn, MA 01801 · 866-885-2462 www.cdimeters.com

FREE SUBSCRIPTION

DIGITAL EDITION FREE WORLDWIDE
PRINT EDITION FREE TO U.S. SUBSCRIBERS



Learn How To Save
Energy & Improve
Productivity In
YOUR Industry!

Subscribe Now!



Subscribe at
airbestpractices.com

BEKO Technologies Remains Ahead of the Curve

This is crucial to our value-based approach, as is the need to put the customer first,” Koch said. “It will continue to be important to our long-term success.”

Ingenuity Runs Deep

BEKO Technologies’ business strategy is rooted in ingenuity, dating to the very

beginning when it pioneered the use of zero air loss condensate drains with the introduction of the BEKOMAT® condensate drain. The company, which was far ahead of the curve at the time when it created the BEKOMAT, developed the technology to help users save energy at a time when energy wasn’t a priority for most.



A wide range of technologies and systems from BEKO Technologies help users efficiently and effectively treat and manage compressed air and compressed gas.



Many BEKO Technologies’ products are manufactured in Neuss, Germany, such as flanges for its line of CLEARPOINT® compressed air filters.

Sticking to its belief in sustainability, BEKO Technologies pushed forward with the concept of zero loss drains, which are now prevalent in compressed air systems today. The drains open on demand to remove condensate and other liquids without allowing any compressed air to escape from the system. The result is often substantial energy cost savings.

Another prime example of being ahead of the sustainability curve is the company's introduction of oil-water separators. The technology – also widely used today – removes oil from condensate so the treated condensate (or effluent) can be safely discharged into the municipal wastewater system.

Strack said the level of innovation required for the development and introduction of technologies unlike anything that came before doesn't happen by chance. In the case of BEKO Technologies, it's rooted in the company culture.

"Part of our culture means allowing for engineering creativity," he said. "You have to have a certain openness for thinking about what's around the corner and developing new ideas. That's definitely something that happens here. That's our environment."

Proving Compressed Air Quality

While BEKO Technologies has established a rich history of innovation in condensate technology, it hasn't rested on its laurels since it's ahead of the curve in compressed air measurement and management.

"It's very important for compressed air users to have systems in place that provide high quality air, and it's equally important to have systems in place that provide proof of clean air," said Strack, regarding the company's pioneering work in instrumentation.

To that end, BEKO Technologies has invested heavily in the development of flow, pressure, pressure dew point and particulate measurement instruments. Additionally, it continues to push the envelope in technologies used to monitor and measure liquid oil and oil vapor in compressed air systems. The METPOINT® OCV compact, for example, lets users continuously and precisely check for residual oil vapor content in compressed air.

Not surprisingly, information is everything at BEKO Technologies when it comes to managing the quality of compressed air. It's why the company has focused in recent years on monitoring systems and sensor technologies that make it easier for users

to visualize, understand, analyze and act on various air quality metrics.

Koch said the company's dedication to monitoring and measurement also means BEKO Technologies will continue to expand its offerings of cloud-based solutions in keeping with the customer demands and the industry's progress toward Industry 4.0.

"It's necessary to know what's going on in a system in order to improve it," Koch said. "We're now laying the foundation for having our products and solutions networked in a way that brings everything together and provides that information through the cloud. That's the next level."

THIS IS EFFICIENCY

Low GWP Refrigerant

Reduced operating costs
Minimized carbon footprint
Maximized energy efficiency

Parker's PoleStar Smart-E (PSE) Series is the most environmentally friendly range of refrigerated compressed air dryers available. Designed to work with low Global Warming Potential (GWP) refrigerant, R513A, PSE complies with the requirements of the United States Environmental Protection Agency SNAP Rules 20 & 21 and European F-Gas Regulation (EU 517/2014). This makes Parker PSE the best choice to protect your investment, the climate and the environment.

Parker
parker.com/igfg
800.343.4048

BEKO Technologies Remains Ahead of the Curve

Diverse Air Purification Solutions

A commitment to take things to the next level also describes how BEKO Technologies has evolved into a major, global manufacturer of diverse air purification solutions.

Today, it offers refrigerant, desiccant, and membrane compressed air dryers engineered to satisfy a wide range of drying temperatures and air quality classes, as well as pressure dew points from 59°F (15°C) to -94°F (-70°C). Additionally, its compressed air filters and water separators are engineered to help users efficiently achieve various levels of compressed air purity.

To keep pace with demand for its air purification technologies, the company

produces highly engineered, high-capacity dryers, such as its Heat of Compression (HOC) and blower purge air dryers, in Germany. It also manufactures high-volume, heatless and blower operated desiccant dryers in the United States, the latter featuring patented, self-adjusting software that adapts to ambient conditions, in addition to its line of unique membrane dryers.

In all, BEKO Technologies operates a total of six manufacturing facilities in Germany, the United States, India and China. Among them is its 30,000-square-foot headquarters operation in Neuss where it manufactures a large portion of its products and systems. The company also operates subsidiaries in Germany, the United States, England, France,

Benelux, China, Japan, Scandinavia, India, and Spain. Currently, BEKO Technologies employs more than 500 people and has 14 sales offices located throughout the world.

The value of having manufacturing operations and sales and service representation in strategic regions cannot be understated, said Strack.

“It allows us to best address the needs of the local marketplace, as well as the standards and regulations for each area – and it gives us different opportunities,” said Strack. “We also prefer to source materials locally, which is in addition to providing quality service at the local level.”

BEKO USA Shines Bright

An area of the world where BEKO Technologies’ business strategy and passion for innovation has led to significant growth in particular is the United States. Since it set down roots in Tulsa, Oklahoma, in 1990, BEKO USA has become the largest and fastest growing subsidiary of the company.

Today, the American headquarters is located in Atlanta, Georgia. The facility there also serves as the manufacturing plant for the company’s DRYPOINT® M membrane dryers, as well as desiccant dryers, oil-water separators, and filtration components. The operation currently employs 87 people working in Engineering, Manufacturing, and Assembly.

BEKO Technologies, Corp. President Tilo Fruth said the formation of BEKO USA more than 30 years ago, positions the company to best meet the needs of customers throughout the United States, Canada, Mexico, and South America. He said the decision also continues to pay dividends in terms of growth, noting BEKO USA’s newly opened Mexico subsidiary.



Cost-saving:

- Eliminate peak power charges
- Improved uptime
- Reduced operational costs
- Lower compressor maintenance costs

Space saving:

- Underground storage up to 600 PSI
- Safer than above-ground
- Saves manufacturing space/land costs

Environmental:

- Food safe applications (NSF)
- Use for oil-free, rotary or PET
- Nitrogen ready





 Certified

Proven:

- 100% performance guaranteed
- Over 10 million KWH saved

The Next Step in Compressed Air Energy Saving

Taking industrial energy efficiency to the next level



Optimize, streamline & safeguard your factory's compressed-air process

Available now in the USA at www.aug-wind.com
442.291.9730 • augwindusa@aug-wind.com



Success in the Americas, said Fruth, has been especially rewarding since it's a unique challenge for any company to put down stakes and grow in a market outside its home base.

"It's difficult in the beginning to step foot in a new country especially when you consider the importance of understanding the market," Fruth said. "But we've been successful and that's because the customer-focused approach is very strong here and we combined that with long-standing innovations that originated at our headquarters in Germany."

Carving a Path

As with any thriving company, BEKO Technologies continues to adapt to the needs of the marketplace and customers, no matter the region or industry served. Additionally, it continues to pursue technologies and opportunities aligned with its strategic focus.

In short, BEKO Technologies is a company that will go where others aren't willing or able to go in order to best serve the industry.

"It's about providing the right solution, whether it's focusing on the lifecycle cost of the system versus the low initial cost, or saving energy and improving potential sustainability, or ensuring air quality. It's something we're founded on and we're going to stick to it as the market continues to catch up," said Koch. **BP**

For more information about BEKO Technologies visit www.bekousa.com

To read similar **Air Purification Technology or Measurement** articles, visit <https://airbestpractices.com/technology/air-treatment> or <https://www.airbestpractices.com/technology/instrumentation>

SEPREMIUM

OIL/WATER SEPARATORS



EPA

✓

Compliant

SEPREMIUM Oil/Water separators are EPA COMPLIANT

- SUPERIOR PERFORMANCE
- RELIABLE SEPARATION OF ALL COMPRESSOR LUBRICANTS
- ANY TYPE OF DRAIN CAN BE APPLIED
- OIL RESIDUE OUTPUT VALUE <10 PPM
- 7 MODELS COVERING A COMPRESSOR CAPACITY UP TO 2500 CFM



OIL/WATER SEPARATORS



SEPREMIUM RANGE
Oil/Water Separators

CONDENSATE DRAINS



NUFORS-XF
Pneumatically operated
Extreme capacity



SMART-GUARD-MINI-AL
Electronic zero air loss drain
With alarm feature



COMBO-D-LUX
Digital timer drain
With ball valve and strainer

AIR SAVING PRODUCTS



LOCATOR-EV
Ultrasonic Air Leak detection



AIR-SAVER 1 & 2
Air leak lock-down

THE CONDENSATE MANAGEMENT SPECIALIST

FOOD & BEVERAGE PROCESSING
& PACKAGING MONTHLY FEATURE

Brewing Energy Conservation at Molson Coors Canada

By Roderick Smith, Compressed Air Best Practices® Magazine

► In 2021, Compressed Air Best Practices® Magazine interviewed members of the Molson Coors Canada team, at their Toronto Brewery, to gain an understanding of the work being done to improve energy efficiency. The team members interviewed were Doug Dittburner (Chief Engineer), Antonio Mayne (Utilities Optimization Engineer) and Khalil Daniel (Engineering Intern).

Good morning, can you briefly describe the Molson Coors Toronto Brewery?

Good morning. The Molson Coors Toronto brewery is the largest brewery in our Canada network and it's one of the largest breweries in Canada. We produce 40 brands of beer packaged in a few different sizes of cans, bottles, and kegs. We perform the full brewing process from receiving raw materials, brewing

and then packaging finished goods. This facility brews 3.3 million hectoliters of beer per year – the equivalent of 980 million 12 oz. cans.

What energy efficiency goals exists at Molson Coors and what are your roles in achieving them?

Molson Coors launched a project in 2016 to analyze our enterprise carbon and energy footprint. We conducted an audit of our operations to help us identify our key sources of emissions and opportunities to reduce our impacts. By 2025, we aim to reduce absolute carbon emissions from our direct operations by 50%, and achieve an absolute carbon emissions reduction of 20% across our supply chain. To support this goal, we are investing in renewable energy solutions and performance tracking technology to support great accountability and visibility in our operations.

Our energy mix here at our Toronto brewery is electrical at 30% of total energy consumption and fuel making up the 70% balance. Refrigeration chillers for a central ammonia system are the largest electrical energy consumer, followed by compressed air and then motors and drives. Natural gas is by far our largest fuel source. Our team acts as a technical resource on all topics utility-related; electricity, fuel, water and secondary utilities like compressed air, refrigeration and steam. We support the powerhouse, maintenance and production teams.

In Ontario, we have a 97% carbon-free electrical grid as our energy sources are hydro and nuclear. In order for our site to reduce carbon emissions, the focus is on fuel. We have many projects focusing on this. Electricity, however, is rather expensive in the province at



Chief Engineer Doug Dittburner “marshalls” a compressed air leak program engaging production and maintenance staff!

an average price of \$0.10 USD per kWh. We believe only California has a higher average cost for electricity in North America.

What key performance indicators are your monitoring to measure energy performance?

Our energy intensity measure in Canada (energy use normalized for production) is kWh per hectoliter (100 liters). In the U.S., they use kWh per barrel (117 liters). I (Antonio) started in this role in 2017 and since then our total (fuel and electricity) energy intensity, at this brewery, has dropped by 20% as of late 2020. We expect it to drop by 30% by the end of 2021 and forecast electrical energy intensity use to drop by 20% during the same time period.

This reflects the corporate decision to prioritize reducing the impact of our operations and to prioritize visibility and accountability. There’s been a lot

of support within the brewery and from the corporate network.

What kind of compressed air measurement and monitoring is done?


Compressed air was identified years ago as an energy-intensive utility and we have focused resources to optimize it’s use. We have four oil-free rotary screw air compressors and run two at a time. Their energy consumption is monitored. The compressed air dryers provide a -40°F (-40°C) pressure dew point which is monitored to ensure air quality.

We also monitor compressed air pressure. We monitor it at the main header and at a few other points downstream where we can pull data. Our average pressure at the header is 105 psig.

We also have local pressure gauges to make sure we have enough pressure.

A Revolution in Compressed Air Automation.

- Allen-Bradley PLC Compressed Air Automation
- Dynamic Air Density Compensation
- Advanced Load Sharing to Maximize Energy Efficiency
- Multiple Header Management Solutions
- 30 Years of Service to Industry
- Open Network Architectures for Ease of Connectivity to the Plant Enterprise and Data Security
- Long Life Cycle for Controls Built on an Open Hardware Platform
- Retrofits for Almost Every OEM Compressor
- Allen-Bradley Based Control Systems for All Types of Air Dryers
- Solutions for Centrifugal, Rotary Screw and Reciprocating Compressors
- AirView Comprehensive Visualization System with Data Management



CASE CONTROLS
A Revolution in Compressor Automation
Phone 812-422-2422
Email solutions@casecontrols.com
casecontrols.com

Brewing Energy Conservation at Molson Coors Canada

Compressed air flow is monitored to measure our demand for compressed air. We have divided up the entire plant into four sections to be monitored. The sections are the brewing area and the three major areas of production

(cans, bottles, kegs). Most of the compressed air flow meters we use are pitot-tube flow meters. They don't have pinpoint accuracy but what we are looking for is changes in trends to identify problems or validate improvements.

We distribute reports to each major department showing their use of compressed air along with targets for use-reductions for each department. Right now, the targets focus on base load reductions of compressed air use – particularly compressed air leaks.

How do you go about reducing the level of compressed air leaks?

We monitor compressed air use in the four sections of the plant at the department level and monitor some individual pieces of equipment. In the brewing area, for example, we have a pneumatic conveying transport system to remove the remaining husks after we use the malt. This system uses blowers with compressed air as the back-up. We monitor this unit to make sure only the blower air (less than 15 psig) rather than our 105 psig compressed air is being used.

Doug is really good at engaging staff in our compressed air leak program. We have free lunches for both finding and fixing a leak. He made tags available for all production and maintenance personnel. When you find a leak you tag it and submit a copy to a raffle box. If you fix a leak your ballot stays in the raffle box permanently. Sooner or later your name will be drawn and the participation is awesome.

Antonio previously worked in maintenance roles – in both the packaging and brewing areas of the brewery. That experience helped tremendously by providing familiarity with the actual operation of most aspects of the brewery. He's worked closely with most of the staff and management and is not an outsider asking for changes. Having this trust already established makes it clear he is providing support to the maintenance team-not looking for problems.

We are entering all our compressed air leaks into our general maintenance system so they



An oil-free rotary screw air compressor at the Molson Coors Toronto Brewery.



Compressed air average pressure, flow and dew point is measured and monitored.

are all tracked. We'll have an identifier in one of the fields and we can see how we are doing, if parts on order and if they scheduled to be fixed. Leaks are in the backlog of maintenance items just the same as fixing a motor. If leaks are on a separate spreadsheet, it can get lost.

One way we find leaks is by scheduling someone to look for leaks during planned stops on the production line, when we take it down for 10-15 minutes. Operators and maintenance use these planned stops to clean and inspect the production lines and they are an opportunity to find compressed air leaks. We also perform dedicated leak inspections. We bought an ultrasonic imaging leak detector – you can see the air leak and it's pretty neat. The image is very clear and makes it easier to find in a noisy environment.

We've been doing compressed air leak detection for a few years now. Since we started, we've seen a 20 to 30% reduction in weekend usage of compressed air – which is how we



Dino DeFilippis, from Airergy Management Services, monitors air compressor energy consumption.

calculate our leak load. We are pretty much idle on weekends and this allows us to make this measurement.

How else have you reduced unnecessary use of compressed air?

We have optimized shutdown procedures and shut down equipment which doesn't need to be on. We also use valves to kill compressed air supply to an entire area, over the weekend, when this area is idle. This way there will be no leaks over the weekend.

Some of our case packers have solenoid valves which can be closed. We like that way better because it's easier for maintenance to turn them open them back up. For operators, we give it to them to do in respective areas. Doug's power engineering team will do valving on a header.

Thank you for sharing Best Practices at Molson Coors. **BP**

For more information about Sustainability at Molson Coors visit <https://www.molsoncoors.com/sustainability/sustainability-reporting>


To read similar **Food & Beverage Industry** articles visit <https://www.airbestpractices.com/industries/food> or <https://coolingbestpractices.com/industries/beverage>

Zero Operating Cost Instrument Quality Air



Sahara Air Products

A Div. of Henderson Engineering Co., Inc.
95 North Main Street
Sandwich IL 60548
800-544-4379 • 815-786-9471
Fax 815-786-6117
www.saharahenderson.com



Choosing a Cooling Tower for Your Application – Crossflow or Counterflow?

By Eric Rasmussen, Senior Product Manager, SPX Cooling Technologies, Inc.

Choosing between crossflow (left) and counterflow (right) cooling towers for your application depends on the factors most important to your project specifications.

► With efficient heat exchange an important requirement in the design of an HVAC system, the type of cooling tower you specify to support your project’s unique cooling goals requires careful consideration. After determining the process parameters required for your application – tonnage, range, and approach – cooling tower capabilities can be analyzed.

Because induced draft crossflow and counterflow cooling towers both have distinct advantages, the design requirements and conditions specific to your application determine the appropriate cooling tower for your project. The fundamental difference between crossflow and counterflow cooling towers is how the air moving through the tower interacts with the process water being cooled. In a crossflow tower, air travels horizontally across the direction of the falling water. In a counterflow tower, air travels vertically upwards in the opposite direction (counter) to the direction of the falling water.


Physical Size – Footprint

Every cooling tower requires a certain volume of air to effectively exchange the heat in the process water. Thus, a cooling tower’s plan area and height must be considered with your specific application in mind.

At cooling capacities up to about 750 tons (3295kW), a counterflow cooling tower with its vertically-stacked components may require

less plan area than a crossflow cooling tower. Beyond the 750 ton mark, because crossflow tower modules are stacked vertically at higher tonnages, a counterflow tower offers little to no advantage in footprint versus a crossflow tower and can sometimes take up more plan area.

Depending on the application, a crossflow cooling tower may require less total area than a counterflow tower even at heat loads less



While structural and mechanical components of crossflow and counterflow cooling towers are similar, application-specific design requirements should determine the tower type.

than 750 tons because of the location and number of air inlets – a crossflow tower has two air inlets compared to four air inlets on a counterflow tower.

Maintenance

Routine maintenance is essential to extend the life of a cooling tower so maintenance accessibility is a consideration. The method by which air interacts with the process water in each tower type creates two different styles of plenum areas. This space has a direct effect on maintenance accessibility.

In crossflow cooling towers, the air flow is turned from the horizontal air inlet direction to the vertical discharge direction behind the fill media. This creates a tall, easily accessible plenum inside the tower for inspection and servicing of the cold water basin, drift eliminators, motor, drive system, and fan at the top of the cooling tower.

Counterflow cooling towers turn the air from horizontal to vertical flow beneath the fill media. While this gives good access to the cold water basin, the rest of the tower is more compact with lower overall height. This creates limited access to the spray system, eliminators, motor, drive system, and fan.

Operating Weight

The overall shipping and operating weights of a crossflow cooling tower may be heavier than a counterflow tower due to the crossflow tower’s larger footprint, additional structural supports and steel casing for ease of maintenance access and additional piping for water distribution. However, lighter capacity cranes are typically required to hoist individual modules, which are stacked vertically at higher tonnages. Potential crane and logistical savings must be weighed against the need for additional picks per cell.

Gravity-Fed and Pressurized Water Distribution

A significant design difference between a crossflow and counterflow cooling tower is the method by which water is distributed over the fill media.

In a crossflow cooling tower the process water is pumped to the top of the tower into the hot water distribution basin. The distribution basin is out of the way of the airstream and is gravity fed. The only driving force behind the nozzles is the hydrostatic head of water above the nozzle itself. One advantage of gravity-fed crossflow water distribution is that it can be cleaned while in operation since it is easily accessible from the outside top of the cooling tower.

In a counterflow cooling tower, process water is pumped into a sealed header box. The header box then distributes the water into branch arms and nozzles, creating a pressurized water distribution system. Unlike a gravity-fed system, a counterflow tower’s water distribution system requires pumps to be shut off to clean the nozzles and the cold water basin. To inspect and clean nozzles, one must enter a crawl space inside the tower.

Variable Flow and Cold-Weather Operation

There are significant energy savings opportunities if a cooling tower can be operated under variable flow conditions. When the conditions allow (reduced heat load or cool ambient conditions), reducing

CLEAN • ENERGY-SAVING • EFFICIENT

**Saving Energy & Reducing Operating Costs,
DX Series Refrigerated Air Dryers
Match Power Consumption to Demand.**



DX Series
400 - 3000 SCFM

Digital Scroll Energy-Saving Refrigeration Compressor

Capacity Modulation Control Reduces Power Consumption Up to 90%

Clean, Dry Air with Minimal Pressure Drop

Altec | AIR  Made In U.S.A.

1-800-521-5351 **www.AltecAIR.com**

Choosing a Cooling Tower for Your Application – Crossflow or Counterflow?

the flow rate over the cooling tower instead of the process keeps the process operating in its most efficient manner. Variable flow, or “turndown,” is a way to maximize the effectiveness of the installed cooling tower capacity for any process flow.

Crossflow cooling towers with outboard water inlets and integral inlet louvers handle very high turndown rates (up to 70% or more). Counterflow cooling tower distribution systems are not as easily modified; up to 50% turndown may be achieved but additional pump head may be required.

Cold-weather operation is of paramount importance when choosing a cooling tower to operate in sub-freezing conditions. Ice formation is an ever present danger and can damage tower components including the high efficiency heat transfer fill media. The effects of ice damage can result in higher condenser water return temperatures and increased chiller energy consumption during peak cooling season.

A crossflow cooling tower performs especially well in cold weather. With its gravity-fed water distribution system – even with turndown as low as 30% of design flow – water can still be evenly distributed across the fill. Even distribution prevents water channeling, ice development, unpredictable performance, scale buildup, and potential damage to the tower. During cold-weather operation, the use of devices such as cups or dams in the hot water basin can keep the heat load toward the weather exposed face of the fill, alleviating ice buildup.


At low-flow operation, a counterflow cooling tower has less head pressure and fewer nozzles to distribute water across the entire cross-section of the fill allowing for uneven distribution. Uneven distribution leads to water

channeling, ice development, unpredictable performance, scale buildup, and potential damage to the tower.

Minimum flow rates are both tower type and model specific. Be sure the cooling tower

manufacturer understands the minimum anticipated flow rate and confirm the tower can handle the required hydraulic range.

Louvers are designed to keep water within a cooling tower. They prevent splash out



The fundamental difference between crossflow and counterflow cooling towers is how the air moving through the cooling tower interacts with the process water being cooled. Air travels horizontally across the direction of the falling water in a crossflow tower. In a counterflow tower air travels vertically upwards in the opposite direction (counter) to the falling water.

which can turn to ice in sub-freezing ambient conditions. Integral louvers incorporated into the fill of some crossflow towers help keep water contained in the fill. This provides no external surface for ice development to occur. Counterflow tower louvers are separate from the fill near the cold water basin. The turbulent water splashing in the cold-water basin can lead to ice accumulation on the louver faces during freezing weather.

Heat Transfer Fill


Both counterflow and crossflow fills can vary in shape and size. The appropriate fill for your cooling tower should be based primarily on water chemistry. Suspended solids, biological growth potential, and information about constituents in the process water that can lead to scaling must be determined early in the design process.

Balancing the performance required by a specific fill material and the water chemistry

of the process water are the significant factors in choosing the right fill and type of cooling tower for your project. The best fill type for your application, either film fill or splash fill, depends on biological growth potential and the level of suspended solids in your source water. Cooling tower manufacturers publish guidelines that can be used to help determine the quality of your process water source.

High-efficiency PVC film fill is typically used in cooling towers with clean water. This fill is manufactured in cross-corrugated sheets that stretch the falling water into a thin film on the surface of the PVC sheet. The water then interacts with the airflow through the tower to facilitate the heat transfer. Because more surface area for air-to-water contact is

CROSSFLOW AND COUNTERFLOW COOLING TOWER DISTINCTIONS
CROSSFLOW ADVANTAGES
Capable of up to 70% turndown
Performs well in cold-weather applications
Water distribution system can be cleaned while tower is in operation
More access for routine maintenance
Uses high efficiency heat transfer fill
COUNTERFLOW ADVANTAGES
Smaller footprint up to ~750 tonnage (with film fill)
Potentially lower operating weight
May be easier to install
Accommodates wide range of fill types to address source water quality



Depending on the application, a crossflow cooling tower may require less total area than a counterflow tower because of the location and number of air inlets; a crossflow tower has two air inlets compared to a counterflow tower's four air inlets.



Air System Products
Filtration Group®
Making the World *safer, Healthier & More Productive*

Robo-Drain

Zero-Loss Condensate Drains
Fully automatic, zero-loss drain protects compressed air systems without electricity. Translucent reservoir for visual assurance of operation and non-clogging, full port drain valve.

BULLETPROOF DESIGN BACKED BY INDUSTRY LEADING WARRANTY



RD750 RD11-T


www.airsyspro.com
716.683.0435
ASPSalesTeam@AirSysPro.com



Choosing a Cooling Tower for Your Application – Crossflow or Counterflow?



A crossflow cooling tower's large plenum area allows easy maintenance.



A counterflow cooling tower's stacked components are less accessible for service.

available, film fill types are more efficient than splash fills.

Film fill is not appropriate for all applications due to its higher propensity for clogging and fouling. Splash fill is more tolerant of dirty water sources but has lower thermal efficiency that requires a larger structure. This often makes it more costly than film fill type towers for a given load.


Clog-resistant film fill provides a happy medium between the efficacy of high-efficiency film fill and splash fill in both thermal performance and clog resistance.

Summary

Choosing between a crossflow and counterflow cooling tower for your application depends on the factors most important to your project specifications. Both types are effective means to support chillers and achieve efficient evaporative cooling with a few distinct design differences. **BP**

Eric Rasmussen is a senior product manager and licensed engineer at SPX Cooling Technologies, Inc., Overland Park, KS.

SPX Cooling Technologies, Inc. is a leading global manufacturer of cooling towers, evaporative fluid coolers, evaporative condensers, industrial evaporators and air-cooled heat exchangers providing cooling solutions, components and technical support for heating, ventilation and air conditioning (HVAC), refrigeration, and industrial process cooling applications for nearly a century. SPX Cooling Technologies and its product brands are part of SPX Corporation. For more information visit www.spxcooling.com



Variable Flow Cups – when operating a crossflow cooling tower in cold weather, devices such as cups or dams in the hot water basin keep the heat load toward the side of the fill exposed to the elements.

To read similar **Cooling Tower Technology** articles visit <https://coolingbestpractices.com/index.php/technology/cooling-towers>

BEST PRACTICES

2021 EXPO NOVEMBER 2-4 CHICAGO, IL
COMPRESSED AIR / VACUUM / COOLING



OPTIMIZE ON-SITE UTILITIES

Powering Automation

Research and Identify Innovations
to Enhance the Efficiency and Reliability of Your Systems

Compressed Air

Air Compressors
Air Compressor Controls
Air Purification & Piping
Condensate Management
Pneumatics

Blower & Vacuum

Aeration Blowers
Industrial Blowers
Vacuum Pump Systems
Inlet Filtration/Oil Separators

HVAC & Process Cooling/Steam

Chillers
Heat Exchangers
Cooling Systems
Cooling Towers
Water Treatment
Boilers
Steam Traps

Motors & Drives • Lubricants • Measurement Instruments • IoT Automation & Monitoring

EXPO HOURS

Tuesday, November 2 12:00-6:00PM


Wednesday, November 3 12:00-6:00PM

SAVE THE DATES ON YOUR CALENDAR!
Located at the modern Schaumburg Convention Center
just 10 minutes from Chicago O'Hare International Airport.

cabpexpo.com

Sponsored by





Isentropic Efficiency of Rotary Screw Air Compressors

By Brian Parks, Fourth Utility Consulting

► Many astute air compressor users have noticed the Compressed Air and Gas Institute (CAGI) air compressor data sheets, dated after June 2020, have a new term listed; isentropic efficiency. Isentropic Efficiency will be the new standard of reference for a true comparison of the overall efficiency of air compressors at any rated discharge pressure. Now users can see which company produces the most efficient product with an easy reference percentage number. The compressed air industry, in conjunction with CAGI, has been trying to make fair comparisons between air compressors for years. Let us go back in history and review this historical progression before we get into explaining isentropic efficiency (IE) in detail.

Background

In the 1970s, when rotary screw air compressors were new to the marketplace, their competition was primarily double acting

reciprocating air compressors. These were very efficient air compressors, at least in the initial years of operation. Clients looked at rotary screw air compressors because the piston machines required lots of expensive maintenance, had vibration related problems and were noisy. Also, most required water-cooling which was becoming more costly over time.

Comprehensive standards for testing the performance of air compressors did not exist in the industry until the early 1990s, when ISO 1217 was the first commonly standard test method implemented. Until that time, air compressor manufacturers tested their machines in slightly different ways. For example, there was no standard for inlet temperature or humidity – which can make a big impact on performance. Some air compressor manufacturers were

only measuring the performance of the bare air end, with none of the losses for the inlet valve, coolers, separators, and coolers. This might mean one manufacturer to another could have a package power performance difference of 5% or more.

During this period of history, some air compressor manufacturers did not even publish rated capacity on their brochures. Subsequent audits of the 1970 – 1980 machines have proven they averaged about 425 CFM per 100HP. The double acting reciprocating machines were producing at least 500 CFM per 100HP. With better technology in rotor profiles and tighter machining tolerances, today's rotary screw machines are getting up to 530 CFM for single stages and 600 CFM for two stages – per 100HP motor size.

Until the mid-1970s, end users did not really pay attention to energy costs because electricity was 3 to 5 cents per kilowatt-hour. Most clients had no idea how much an air compressor costs to operate because it was only a small part of a larger bill. Many of the installations employed oversized piston compressors. When they were replaced with less efficient rotary screw machines it did not manifest in any significant change to the power bill. Everyone was simply overjoyed by the lower maintenance cost.

In the 1990s all vendors had their capacities posted on their brochures, but the published capacities varied considerably. For example; one company had a 100 HP compressor rated at 563 CFM at 100PSI, while the rest of the industry was averaging about 490 CFM. Eventually it was found that this particular model was using a 1.40 service factor motor, running at over 125 HP shaft power. It was performing as published but the actual power used was not clear to the customer.

Motor service factors and HP or KW rating has been an evolving subject also. The majority of the industry was using 1.15 service factor motors and using about 10% of the available 15%. Service factor is really the maximum amps, available at a given voltage, that the motor can reliably deliver, given the other design conditions of temperature, altitude (cooling capacity of the air) and Power Factor. Motor manufacturers will nameplate motors any way the customer desires i.e. a 100 HP 1.25 SF motor or a 125HP 1.0 SF are essentially the same motor if in the same frame size. The air compressor manufacturers select and apply the motors for their compressors in many different ways, but the maximum amps available at a rated voltage is the final determining factor.

In the 1980s the industry became more exacting in what was meant by flow. One company started publishing “free air delivery” or FAD, which measures the air at the inlet and published the total power used. They looked less efficient than the others, but they were really about the same.

This article is not casting any dispersions on any of the air compressor manufacturers. They were all publishing good data, they just measured in different ways!

ISO 1217 Annex C

Originally published in 1947, the CAGI Handbook has been the go-to resource for everything compressed air. Now in its seventh edition, and available electronically on the

CAGI website, the illustrated handbook contains engineering information from leading manufacturers and valuable reference data about compressed air systems. In the late 1990s, CAGI and their member companies agreed upon a standard where they would measure their machines to the same criteria. CAGI settled on the globally accepted ISO 1217 Annex C, which is the base standard still used today. This test is for the volume flow through an air compressor. CAGI and Pneurop have adopted a definition for Standard Air that is 20 degrees C, 1 bar absolute, and 0% RH. When testing to 1217, you correct back to the inlet conditions of the compressor to calculate the volume that flowed through the compressor. If you want to know the mass that flowed through the compressor, you have to convert



Isentropic Efficiency of Rotary Screw Air Compressors

the volume flow to standard conditions. That gives you the SCFM (mass) flowing through the compressor at any given ambient conditions.

CAGI Air Compressor Data Sheets

Once ISO 1217 Annex C was accepted, CAGI and their members agreed to publish a simple standard datasheet for fixed speed compressors that looks like the following. See figures A and B. As part of the CAGI Performance Verification Program, member companies are required to post these datasheets on their website with easy access for customers. An independent testing lab goes to each air compressor manufacturer and randomly selects three compressors to be shipped to the lab. The lab then tests those compressors and verifies that their performance matches the published

data sheets. The results of all the tests are available at <https://www.cagi.org/pdfs/cagirotarydirectory.pdf>

Let's examine the lubricated, fixed-speed rotary screw air compressor data sheet (see Figure A). Variable speed air compressors have data sheets in the same format, but their isentropic efficiency uses a weighted average of full load, 40 percent, and 70 percent of full load.

- Items 1 & 2: manufacturer's name and model, type of cooling (water or air-cooled) and whether it is a single or two stage compressor.
- Item 3: flow capacity at full load. That number is the amount of cubic feet measured at the discharge, adjusted to

the inlet conditions at the time of the test per ISO 1217 Annex C.

- Item 4: full load operating pressure. This is the pressure where the capacity and total package power is measured.
- Item 5: maximum full flow pressure. On machines with a load/unload operating system, this is the highest pressure at which the machine will operate before the machine unloads. For this type of machine, this pressure can be 3 to 15 PSI higher than the full load operating pressure. At this pressure, the machine's total package power will be higher.



Worried About Moisture & Oil Contamination in Food Production?

Learn Quality & Safety Best Practices – View Our
FREE* On-Demand Webinars & Articles

Library of Food Safety Webinars Includes

- Safety and Quality in Compressed Air: Why You Should Care
- Integrating ISO 8573-1 Compressed Air Quality Classes into SQF Food Safety Certification
- Safe Quality Food Standard: 5 Compressed Air Criteria
- Global Food Safety Initiative (GFSI) Compliance: Two Compressed Air System Specifications

Library of Food Safety Articles Includes

- Compressed Air GMPs for GFSI Food Safety Compliance
- Sampling and Testing for Compressed Air Contaminants
- Unilever Ice Cream Plant Reduces Compressed Air Consumption
- Keep Contaminants Out of Food & Bev Processing Air Supplies

*Included with your free magazine subscription

- Items 6 & 7: nameplate horsepower (HP) of the main drive motor and the efficiency of the motor. The higher number Item 7 is, the more efficient the motor. Some manufacturers have an option for higher efficiency motors.
- Items 8 & 9: fan motor nameplate HP and efficiency. The fans are normally designed to operate at 40°C (104°F). If the air compressor is in a warmer location, a larger fan may be required.
- Item 10: total package operating power when there is no demand on the compressor. This is very important for calculating the efficiency of a load/unload compressor at partial load conditions.
- Item 11: full load operating power in kilowatts, measured at the full load operating pressure. Includes fans, controls and any other device in the package using energy.
- Item 12: package specific power is the amount of kilowatts required to make one hundred (100) CFM. The lower the number-the more efficient the machine.
- Item 13: isentropic efficiency-which will be explained later. The higher the number is, the more efficient the air compressor is. Figure A is the format of the current fixed speed data sheet. The original data sheets, that started in 2002, had less information.

Don't Get Left Behind – Get Certified!

Are you an expert in the compressed air industry? Holding the status of being a Certified Compressed Air System Specialist demonstrates that you have the knowledge and expertise in compressed air systems that sets you apart and gives confidence to the customers you serve.



Take the exam and get certified. Learn more and find how to get certified at the Compressed Air & Gas Institute's (CAGI) website: www.cagi.org/personnel-certification



COMPRESSOR DATA SHEET					
In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors					
Rotary Compressor: Fixed Speed					
MODEL DATA - FOR COMPRESSED AIR					
1	Manufacturer: ABC Compressor				
2	Model Number:	12A 22B 40 - 125 psig / 460V/3ph/60Hz		Date:	8/12/19
	<input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled			Type:	Screw
				# of Stages:	1
3*	Rated Capacity at Full Load Operating Pressure ^{a, c}		175.0	acfm ^{a, c}	
4*	Full Load Operating Pressure ^b		125	psig ^b	
5	Maximum Full Flow Operating Pressure ^c		125	psig ^c	
6	Drive Motor Nominal Rating		40	hp	
7	Drive Motor Nominal Efficiency		93.6	percent	
8	Fan Motor Nominal Rating (if applicable)		1.3	hp	
9	Fan Motor Nominal Efficiency		80	percent	
10*	Total Package Input Power at Zero Flow ^c		9.1	kW ^c	
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^e		36.12	kW ^d	
12*	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e		18.69	kW/100 cfm ^c	
13	Isentropic Efficiency		72.77	Percent	

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with control strategy.
- Tolerance is specified in ISO 1217, Annex C, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	
1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/- 10%
Above 15	Above 529.7	+/- 4	+/- 5	

Member

ROT 030.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

Figure A. Sample CAGI Data Sheet for a lubricated, fixed speed rotary screw air compressor.

Isentropic Efficiency of Rotary Screw Air Compressors

The capacity ratings have a tolerance of up to 7% for capacity and 8% for specific power. The tolerance goes lower for larger air compressors. A tolerance is required because it is impossible to make a compressor that will produce the same flow at the same power consistently.

Air Compressor Isentropic Efficiency

The specific power item, in the data sheet, is a calculation intended to show the most efficient compressors. The calculation is (total package KW x 100)/ CFM. The lower the specific power, the more efficient the package. Using specific power for comparison works perfectly if the compressors have the same full load pressure rating. The problem is that many

of the compressor manufacturers rate their compressors at different pressures as shown in Figure 1.

The Energy Policy and Conservation Act, as amended, (EPCA) covers certain commercial and industrial equipment, including

Brand A	100	123 - 125	150	174 - 175	195 - 200	—
Brand B	100	115	125	135	150	190
Brand C	100	125	150	175	200	—
Brand D	115	150	165	—	—	—
Brand E	100	110 - 115	125	150	175	200

Figure 1. Pressures used (psi) for power ratings of lubricated fixed speed rotary screw air compressors.

Register Now!

GLOBAL EVENT SPONSORS

AISTech[®]

THE SYSTEMS GROUP

The Iron & Steel Technology Conference and Exposition

29 June–1 July 2021 / Nashville, Tenn., USA

compressors, for which the Department of Energy (DOE) is authorized to establish energy conservation standards. DOE has determined that EPCA covers commercial and industrial air compressors and has been considering energy conservation standards and test procedures for such equipment. In January 2020, DOE has published a Federal Register notice of final rule pertaining to energy efficiency

standards for compressors, titled 85FR1504. CAGI and their members fully support the use of isentropic efficiency as the standard of comparison on compressor efficiency. The simplest way to define isentropic efficiency is shown in Figure 2.

$$\eta_{isen} = \frac{16.52 \times \left(\left(\frac{P_2 + 14.5}{14.5} \right)^{0.2857} - 1 \right)}{P_{Spec}}$$

η Stands for Efficiency. "isen" is an abbreviation for isentropic.

Figure 2.

Comparing Isentropic Efficiency

This isentropic calculation is based on full load operation only for fixed speed compressors. The highest isentropic efficiency currently published is about 92% and the lowest about 50%. In general, machines above 100 HP have a higher average IE than do those with lower HP. This is because two stage compressors

**SPECIFIC POWER VS. ISENTROPIC EFFICIENCY
SINGLE-STAGE COMPRESSORS**

Compressor	Drive Motor Nameplate Rating	Maximum Full Flow Operating Pressure	Full Load Operating Pressure	Rated Capacity at Full Load Operating Pressure	Input kW @ Rated Flow and PSIG	Specific Power kW/100 cfm	Isentropic Efficiency %
A	100 hp	157	150	435	87.2	20.00	82.55
B	100 hp	145	135	465	89.8	19.31	81.10
C	100 hp	115	100	520	91.0	17.50	75.94
D	100 hp	150	150	415	96.3	23.15	71.45
E	100 hp	110	100	466	91.3	19.60	67.82

Figure 3.

**SPECIFIC POWER VS. ISENTROPIC EFFICIENCY
TWO-STAGE COMPRESSORS**

Compressor	Drive Motor Nameplate Rating	Maximum Full Flow Operating Pressure	Full Load Operating Pressure	Rated Capacity at Full Load Operating Pressure	Input kW @ Rated Flow and PSIG	Specific Power kW/100 cfm	Isentropic Efficiency %
A	150 hp	125	125	738	129.9	17.60	85.37
B	150 hp	100	100	890	141.6	15.90	83.53
C	150 hp	200	190	596	135.1	22.70	82.30
D	150 hp	150	150	680	138.0	20.40	81.10
E	150 hp	100	100	826	139.5	16.90	78.70

Figure 4.

**FREE
SUBSCRIPTION**

DIGITAL EDITION FREE WORLDWIDE
PRINT EDITION FREE TO U.S. SUBSCRIBERS



**Learn How To Save
Energy & Improve
Productivity In
YOUR Industry!**

Subscribe Now!



Subscribe at
airbestpractices.com

Isentropic Efficiency of Rotary Screw Air Compressors

HP	BEST	AVERAGE	WORST
10	72	53	49
15	75	63	54
20	76	68	57
25	80	68	63
30	79	68	63
40	82	72	62
50	82	74	63
60	82	74	63
75	81	75	67
100	86	77	65
125	88	79	62
150	87	79	68
200	92	80	70
250	90	83	70
300	92	82	70
350	90	81	69

Figure 5. Isentropic efficiencies, by horsepower, for lubricated, fixed-speed, rotary screw air compressors. Based on CAGI datasheets dated up to January 2021.

typically start at 100 HP and have higher isentropic efficiencies. With IE, a user can compare a 100PSI compressor to a 150 PSI machine to see which is more efficient. As of July 2020, all CAGI members who participate in the performance verification program have the isentropic efficiency posted on their CAGI datasheets. Above 250 HP, isentropic efficiency is not required on the datasheets, so we used calculated IE for this comparison. Figure 3 shows a comparison of 100 HP compressors at all different pressures. These are sorted by the isentropic efficiencies. As you see, lower specific power does not necessarily indicate lower isentropic efficiency. Figure 4 shows the same comparison of two-stage compressors and in general they have a higher isentropic efficiency.

Isentropic efficiency comparisons will keep the compressed air industry working to improve efficiencies which in turn will save lots of energy in the future. Someday you may see the DOE or state governments requiring a minimum isentropic efficiency level for a compressor to be sold. **BP**

About the Author

Brian Parks has worked in the compressed air industry for over 45 years. He has worked in service, sales, machine testing, engineering and regional management

in both the US and abroad for two different air compressor manufacturers. After retiring, he started Fourth Utility Consulting, initially doing distributor training, auditing and audit reviewing. Later, the company started doing consultation for compressor companies to help establish the most efficient products by using CAGI datasheet comparisons to increase efficiency. Fourth Utility has a database of over 6,500 archived data sheets, which are used for correct auditing and auditing reviews.

For more information contact Brian Parks, President, Fourth Utility Consulting, email: 4thutilityconsulting@gmail.com


For more information on this topic, visit CAGI's website to view the educational video on isentropic efficiency at <https://www.cagi.org/education/videos.aspx>

Host a CAC L1 Training ONLINE TODAY

Interested in hosting the Fundamentals of Compressed Air Systems (L1) training online? CAC instructors are now able to provide the L1 training online! Contact us today to get your training scheduled! CAC will work with hosts to identify dates, times and available instructors.

Like the popular in-person class, the web-based workshop is designed to teach facility engineers, operators, and maintenance staff how they can achieve 15-25 percent cost savings through proper operation and controls, system maintenance, and appropriate uses of compressed air. Both the in-person and web-based classes utilize the same basic content and adhere to the CAC's principles of product-neutrality and a focus on the systems approach to managing compressed air.

For more information, please contact CAC Executive Director, Tracey Kohler at tkohler@compressedairchallenge.org.



- /CACKnowPressure
- /company/compressed-air-challenge
- /CACKnowPressure

To read similar **Air Compressor Technology** articles visit <https://www.airbestpractices.com/technology/air-compressors>

Worried About Moisture & Oil Contamination in Food Production?

Learn Quality & Safety Best Practices - View Our **FREE* On-Demand Webinars**



Our Extensive Library of Webinars Includes These Titles

- Safety and Quality in Compressed Air: Why You Should Care
- Safe Quality Food Standard: 5 Compressed Air Criteria
- Integrating ISO 8573-1 Compressed Air Quality Classes into SQF Food Safety Certification
- Global Food Safety Initiative (GFSI) Compliance: Two Compressed Air System Specifications

*Included with your free magazine subscription

Get FREE Instant Access* at airbestpractices.com/magazine/webinars

COMPRESSED AIR INDUSTRY & TECHNOLOGY NEWS

Kaeser CNC Line of Booster Compressors

Announcing Kaeser's new CNC line of booster compressors, delivering capacities from 28-281 cfm with pressures up to 650 psig. These fully enclosed and integrated units are available in 10-30 hp models. This product line expansion also adds the DNC-XL, bringing Kaeser's advanced booster lineup to nine models with flows ranging from 28-882 cfm. Each package includes a built-in aftercooler for optimized cooling and a sound-dampening enclosure for reduced noise levels and better machine protection. A reduced footprint, easy access design and simple connections make installation and maintenance a breeze. A complete sensor array and the Sigma Control 2 controller offers unsurpassed control and monitoring with enhanced communications capabilities for seamless integration into remote plant control/monitoring systems. All Kaeser booster packages can be ordered for nitrogen compression or as a water-cooled unit and can be customized for specific applications with optional variable speed drives and integral Eco-drains.



Kaeser Compressors, <https://us.kaeser.com>

Hertz Kompressoren USA Oil-Free Scroll Packages

In honor of their 5-year anniversary, Hertz Kompressoren USA is excited to announce their new HS Series scroll compressors. Hertz prides itself on its flexibility and adaptability in meeting market demand. Eyeing an opening in the market, Hertz decided to manufacture a line of completely oil-free scroll packages to serve industries such as laboratory & life science, medical, food & beverage, and countless others. HS Series package units come in a 2-40 HP range boasting low noise levels, trouble-free maintenance and compact foot prints. With an eye on the future, Hertz believes that this is only the beginning. "I see us growing even more over the next five years, both with Channel Partners and as a company with our employees," said Stephanie Brockman, Chief Operations Officer.



Hertz Kompressoren USA,
www.hertz-kompressoren.com

Xebec Acquires Nortec

Xebec, a global provider of clean energy solutions, is pleased to announce on April 30, 2021, it has closed the acquisition of all the outstanding shares of Tennessee based Nortekbelair Corporation. Nortec's principal, Mike Zarif, Ph.D., will remain with Nortec after the acquisition and continue his focus on R&D and product development within the company. With this acquisition, Xebec's manufacturing footprint will expand with an 18,500 sq. foot facility in Maryville, Tennessee, and will provide the company with key personnel to establish a "Center of Excellence" for its dehydration products comprised of compressed air dryers, renewable natural gas dryers, hydrogen dryers and support its Cleantech Service Network. Total consideration payable by Xebec is approximately \$8.5 million CAD through a combination of cash on hand, of which \$2.6 million CAD was paid in cash on closing, and 735,838 common shares of Xebec at a price of \$4.385 per common share were issued to the seller.

Xebec Adsorption, www.xebecinc.com

Total Equipment Instrument Air Compressor Buildings

Total Equipment Company, a distributor and service provider of fluid- and air-handling products, is delivering custom-engineered Instrument Air Compressor Buildings to support many industries in their region. TEC



is a trusted name, servicing industries in Pennsylvania, West Virginia, Ohio and beyond, with a broad inventory of pumps, compressors, blowers, mixers and mechanical seals for over 39 years. TEC has custom-engineered Instrument Air Compressor Buildings for customers in their region for more than ten years. With extensive machine and fabrication capabilities in-house, TEC staff mounts complete compressed air systems to steel decks, followed by roof and side paneling assembly. Each building is engineered-to-order, compliant with seismic and wind loads to area classification, delivering instrument air standard-compliant compressed air.

Total Equipment Company, www.totalequipment.com

COMPRESSED AIR INDUSTRY & TECHNOLOGY NEWS

Donaldson Ultrapac Smart Dryer

Donaldson Company, Inc, a leading worldwide manufacturer of innovative filtration products and solutions, introduced the Ultrapac Smart dryer, a solution that removes condensate and dries compressed air streams in manufacturing facilities using three stages of separation: filtering, drying and purifying. Highly purified compressed air is critical for food and beverage process applications, like beer, bottled water, milk, wine and yogurt. The Ultrapac Smart dryer design accommodates unique location and spatial conditions, enabling configurations that fit among large equipment, conveyor lines and other machines. With three versions – Superplus, Plus and Standard – and a modular design, the dryer can be installed vertically, horizontally or on a wall. As a compact, stand-alone, plug-and-work solution, all of the Ultrapac Smart dryer's components, including the filter elements and the desiccant cartridge, are easy to access and replace.



Donaldson Company, www.Donaldson.com

Festo MS Series Filtration Products

Festo introduces the MS series of filtration products – filters that lower the risk of particle contamination when compressed air comes into direct contact with food or packaging in the food zone. The MS series meets or exceeds the highest industry standards for clean air. Always in stock with guaranteed fast shipping, MS filters arrive assembled with safety and total productive maintenance features typically found as custom add-ons. The units install easily and are priced competitively. The MS series is designed for food and packaging-in-food-zone applications in the dairy, baking, produce, processed foods, pet foods, craft beer, cold food processing, and beverage industries. Furthermore, this versatile series is suitable for a wide range of industries outside of food and beverage where clean compressed air enhances the longevity and efficient operation of pneumatic cylinders and processes.



Festo, www.festo.com

Augwind New Subsidiary in the USA

In great news for industrial manufacturers, Augwind, an innovative Israeli company specializing in advanced compressed air technologies, has opened its first USA subsidiary. Augwind, with global headquarters in Israel, was founded in 2012 by Or Yogev, a graduate of the California Institute of Technology with a focus on thermodynamics. Industrial plants rely heavily on compressed air to run their operations, with such systems accounting for up to 20% of a plant's energy use. Most of the time, that use is inefficient and costly. Augwind's unique energy-saving technology has already saved current customers over 10 million kWh and is now available for the first time in the USA. Leading Augwind's foray into the US market is Larry Wilson, an expert with over 35 years in the compressed air industry.



Augwind, www.aug-wind.com

Ingersoll Rand Sells High Pressure Solutions Segment

Ingersoll Rand Inc., a global provider of mission-critical flow creation and industrial solutions, has entered into an agreement to sell a majority interest in its High Pressure Solutions Segment to the private equity firm American Industrial Partners. Ingersoll Rand will receive cash proceeds of approximately \$300 million at closing for its majority interest and will retain a 45% common equity interest in the business. The transaction, subject to standard closing conditions, is expected to be completed in the first half of 2021. "Today's transaction is a meaningful step forward in our transformation and achieves many of the goals we have previously communicated," said Vicente Reynal, chief executive officer of Ingersoll Rand. "It significantly reduces our direct exposure to the upstream oil and gas market to non-material revenue exposure of <2%, and accelerates our ESG commitments."

Ingersoll Rand, www.IRCO.com

CHILLER & COOLING INDUSTRY & TECHNOLOGY NEWS

Portable Air-Cooled Chillers

Frigel is introducing air-cooled portable chillers into its product line. With chilling capacities from 3.5 to 15.5 tons, the eight-model product line has the broadest operating temperature range available today, from 23°F to 77°F. In addition, the MRS chillers are uniquely designed for both indoor and outdoor applications. Designed for maximum ambient temperatures from 113°F to 122°F, the chillers offer high performance at high ambient conditions. The MRS unique condenser design also offers customers several measurable operational advantages. With dB(A) ratings of 48 to 58, the MRS is the quietest chiller on the market with fans that eliminate problems associated with dB(A) ratings greater than 85. Standard with the product line is its unique non-ferrous water contact surfaces design which features stainless steel brazed plate evaporators and pumps with stainless steel coolant contact surfaces.



Frigel, www.frigel.com

BluEdge Digital Service Platform

Carrier is launching a new tiered service offering to complement its existing BluEdge service platform: BluEdge Digital. The new digital offering, which can stand alone or be added to existing BluEdge service agreements, connects customers' equipment to Carrier's cloud-based IoT platform, providing them with advanced analytics and actionable insights to visualize, advise and optimize machine health and life cycle outcomes. That includes OnDemand service request capability, web / mobile real-time chiller dashboards, prioritized alarm and alert notifications, and performance and vibration reports. More advanced digital solutions including remote monitoring, performance optimization and predictive services are provided in the Enhance and Elite tiers, while BluEdge Digital Elite tier customers with connected chillers will receive continuous support from BluEdge Command Centers, remote teams of data scientists and engineers that provide real-time monitoring of building and equipment operations.



Carrier, www.carrier.com

High-SST Turbocor Compressors

Danfoss has expanded the capabilities of Turbocor compressors TTS and TGS with a higher saturated suction temperature (SST) operating range – helping OEMs bring the benefits of oil-free technology to data centers operating at higher temperatures. Available on TTS and TGS compressors designed for both air-cooled and water-cooled chillers, the new high-SST option enables select Turbocor models to generate leaving water temperatures as high as 82°F, substantially reducing compressor load and power consumption. This change enables OEMs to offer next-generation operators all the benefits that have made Turbocor oil-free compressors a proven, successful choice for data center chillers – such as efficiency, accuracy, and long-lasting reliability with no performance degradation over time. The newly equipped Danfoss Turbocor models are designed for use with A1 and A2L low-GWP refrigerants R134a, R515B, R513A, and R1234ze.



Danfoss, www.danfoss.com

Outdoor Pumps with Permanent Magnet Motors

Armstrong Fluid Technology has announced that Design Envelope pumps with Permanent Magnet motors up to 10hp are now available NEMA 4X/IP66 rated, for outdoor installation. Featuring advanced performance mapping technology and load-limiting logic, the new pumps reduce energy consumption by as much as 30% compared to pumps supplied with a loose variable speed drive. Together with new more efficient pump hydraulics, the new 1 to 10hp pumps can save an additional 20% compared to competing integrated products with induction motors. Features of the new Design Envelope outdoor pumps include overhead weather shield to protect motor fans, a cover to protect touchscreen user interface, TL approved factory tested NEMA 4X rated controls, parallel sensorless control providing additional energy savings, available Pump Manager service and more.




Armstrong Fluid Technology,
www.armstrongfluidtechnology.com

CHILLER & COOLING INDUSTRY & TECHNOLOGY NEWS

Biodegradable Scale Remover

EcoClean Scale Remover is one of the fastest acting products on the market for dissolving heavy scale, corrosion, and naturally occurring oxides off metals. It is effective and safe to use on iron, carbon steel, stainless steel, copper, aluminum, magnesium, and their alloys. It improves heat-transfer efficiency by creating clean surfaces on all heat-exchanger equipment and improving water flow in obstructed pipes. Powerful corrosion inhibitors contained in the scale remover protect treated metals from flash rust. As an added bonus, EcoClean Biodegradable Scale and Rust Remover Powered by Nano-VpCI is a USDA Certified Biobased Product that contains 100% USDA certified biobased content. It meets minimum biobased content requirements under the mandatory federal purchasing initiative of the USDA BioPreferred Program, making it ideal for use by federal agencies and their contractors.



Cortec Corporation, www.cortecwatertreatment.com

Rogers Mechanical Contractors Acquires R&D Mechanical Services

Rogers Mechanical Contractors (Rogers) announced its acquisition of R&D Mechanical Services, a Ball Ground, GA based provider of commercial HVAC preventive maintenance, repair, and retrofit/replacement services in the Greater Atlanta area, with a particular focus on the distribution center market. Rogers is a leading HVAC/mechanical and plumbing contractor headquartered in Villa Rica, Georgia and serves customers across the country, for which this acquisition further enhances its product offerings. Effective immediately, R&D Mechanical Services will begin operating as Rogers Mechanical Contractors. As part of the transaction, all employees of R&D Mechanical Services will be retained and new additional employment opportunities will be posted online.

Rogers Mechanical Contractors, www.rmciqa.com

Emerson Joins the Carrier Alliance Supplier Program

Emerson has joined the Carrier Alliance program. As part of the program, Emerson will continue to provide leading-edge software and technologies from its air conditioning and cold chain businesses, such as compressors, valves, and sensors, to a range of products throughout the Carrier portfolio. Emerson and Carrier will continue collaborating to develop and deploy a robust set of leading technologies and solutions throughout Carrier's HVAC and Refrigeration segments serving residential, commercial and transportation markets. Carrier has long leveraged Emerson's Copeland compressors, White-Rodgers valves, controls and thermostats, and Thermo-O-Disc sensors in its products. Emerson's Copeland Compressors have been integral to Carrier's product portfolio and will be a critical component of Carrier's offering to meet or exceed higher Season Energy Efficiency Ratio (SEER) rating requirements beginning in 2023.

Emerson, www.emerson.com

Embraco Celebrates 50-Year Anniversary

In March, Nidec Global Appliance celebrated the anniversary of one of its brands: Embraco, a name globally known as a reference in refrigeration technology for the home appliances and commercial cold chain since 1971. The product brand completes half a century of its innovative approach and is ready to refresh the future. After being acquired by Nidec Corporation, in July 2019, Embraco was integrated into the Nidec Global Appliance division, gaining a structure to accelerate growth. Nidec Global Appliance is organized into three business units (BU): Home Appliances, Commercial Appliances and HVAC. This segmentation gives Embraco the opportunity to operate with a more dedicated focus on specific market segments, strengthening its customer centric approach and improving its portfolio of compressors and condensing units.



Embraco, www.embraco.com

BEST PRACTICES

2021 EXPO NOVEMBER 2-4 CHICAGO, IL
COMPRESSED AIR / VACUUM / COOLING



OPTIMIZE ON-SITE UTILITIES

Powering Automation

Research and Identify Innovations
to Enhance the Efficiency and Reliability of Your Systems

Compressed Air

Air Compressors
Air Compressor Controls
Air Purification & Piping
Condensate Management
Pneumatics

Blower & Vacuum

Aeration Blowers
Industrial Blowers
Vacuum Pump Systems
Inlet Filtration/Oil Separators

HVAC & Process Cooling/Steam

Chillers
Heat Exchangers
Cooling Systems
Cooling Towers
Water Treatment
Boilers
Steam Traps

Motors & Drives • Lubricants • Measurement Instruments • IoT Automation & Monitoring

EXPO HOURS

Tuesday, November 2 12:00-6:00PM

Wednesday, November 3 12:00-6:00PM

SAVE THE DATES ON YOUR CALENDAR!
Located at the modern Schaumburg Convention Center
just 10 minutes from Chicago O'Hare International Airport.

cabpexpo.com

Sponsored by



THE MARKETPLACE

TECHNOLOGY & JOBS

Job & Product Marketplace Advertising Information

Reach 16,000+ readers of **Compressed Air Best Practices® Magazine with Marketplace Ads every month!** Job Marketplace ads are also placed for one month on www.airbestpractices.com and promoted in our three monthly e-newsletters.

Ad dimensions are 2.36" wide x 3.91" tall. We can help you design the ads. Send us your logo, product photo, and text to rod@airbestpractices.com. We recommend 20-50 total words of text.

Prices are \$300.00 per Job Marketplace Ad and \$350.00 per Product Marketplace Ad (\$300 if 6 or more ads are placed). Contact Rod Smith at rod@airbestpractices.com to schedule your Marketplace Ads.



COMPRESSED AIR BEST PRACTICES® www.airbestpractices.com

ADVERTISER INDEX

Company	Page	Web Site
Kaeser Compressors	Outside Back Cover	https://us.kaeser.com/cabp
Atlas Copco	Inside Front Cover	www.atlascopco.com/air-usa
BEKO Technologies	Inside Back Cover	www.bekousa.com
Mikropor	5	www.mikroporamerica.com
SMC	7	www.smcworld.com
Quincy	9	www.quincycompressor.com
Yaskawa	11	www.yaskawa.com
Clean Resources	12	www.cleanresources.com
Sullair	13	www.sullair.com
Hertz Kompressoren USA	15	www.hertz-kompressoren.com
Anest Iwata	17	www.anestiwata.com
Sullivan-Palatek	19	www.sullivan-palatek.com
CDI Meters	21	www.cdimeters.com
Parker	23	www.parker.com/igfg
Augwind	24	www.aug-wind.com
Jorc Industrial	25	www.jorc.com
Case Controls	27	www.casecontrols.com
Sahara Air Products	29	www.saharahenderson.com
Altec AIR	31	www.AltecAIR.com
Air System Products	33	www.airsyspro.com
Aignep	37	www.aignepusa.com
Compressed Air and Gas Institute	39	www.cagi.org/personnel-certification
AISTech 2021	40	www.aist.org/conference-expositions/aistech
Compressed Air Challenge	42	www.compressedairchallenge.org
Best Practices 2021 Expo & Conference	14, 35, 48	www.cabpexpo.com
Best Practices Webinars	16, 38, 43	www.airbestpractices.com/magazine/webinars

Advertising/Editorial **Rod Smith** • rod@airbestpractices.com • Tel: 412-980-9901
 Subscriptions Administration **Patricia Smith** • patricia@airbestpractices.com • Tel: 412-980-9902
 A Publication of **Smith Onandia Communications LLC**
 37 McMurray Rd., Suite 106, Pittsburgh, PA 15241

THE MARKETPLACE

TECHNOLOGY & JOBS

High Efficiency Compressor Controllers

Control Rotary Screw, Vane, Scroll or Recip Compressors



Save Energy controlling up to FOUR compressors and qualify for **Utility Rebates.**

- Automatic Lead/Lag Control-up to FOUR Compressors
- Accurate Pressure Control with Pressure Transducers
- Compressors and Vacuum Pumps from 1 to 250 hp
- Automatic Lead/Lag Control for Chillers & Heat Exchangers

Standard Pneumatic Products, Inc.
Tel: 203-270-1400 • Toll free: 800-979-9156
Email: sales@stdpneumatics.com
www.stdpneumatics.com

Superior[®] AccuTrak[®] Ultrasonic Inspection Systems

The Ultimate Air & Gas Leak Detector



AccuTrak[®] VPX-WR

Find Compressed Air Leaks Fast!

- Also any Gas, Refrigerant or Vacuum.
- Rugged Design for Harsh Environments
- Sealed to Resist Water, Oil, Dust & Chemicals
- Professional's Choice for Air Leak Surveys

SuperiorSignal.com/CA

Storm[®] BLOW-OFF STATIONS



Safe De-Dusting of Employees

OSHA Compliant - only 2.5 PSI

Eliminates Misuse of Compressed Air

800.490.2401

www.personnelblower.com



Use coupon code **air10** for 10% off the internet price.

Sauer Compressors USA RENTALS



- Air & Gas Compressor Skid Packages
- Containerized CNG Packages
- Containerized Air Packages
- Breathing Air Packages
- High-Pressure Hoses
- Weather Enclosures
- Refrigeration Dryers
- Outlet Filtration

WHY RENT SAUER?

- Customized Solutions
- Reliable State-of-the-Art Machines
- Repairs & Maintenance Covered
- Reduce Downtime
- Receive 24/7 Support

Dependable up to 7,000 psi - anywhere, anytime, anygas.
sales@sauerusa.com | 410.604.3142 | www.sauerusa.com

Engineered Purification Compressed Air Products www.alpha-pure.com 877-645-7676



CONDENSATE DRAINS

- Timer Controlled
- Zero Loss
- Float Drains

DEW POINT SENSORS S211 / S215 / S220



UNIQUE SENSOR ELEMENTS

- Various measuring ranges available from -100 ... +50 °C Td
- Compact size makes them ideal for dryer installations
- Optional display for on-site values. Display can be rotated 340° horizontally to fit your needs
- Signal output supported: 4 ... 20 mA 2-wire, 4 ... 20 mA 3-wire, or 4 ... 20 mA 3-wire + Modbus RTU
- IP65 casing provides robust protection
- Low maintenance costs due to stable and reliable measurements which increase calibration intervals

www.suto-itec.com



SMALL CAUSE - LARGE EFFECT

Functional principle

Leaks are points in the compressed air system where air can escape. As this results in a pressure drop, more energy is needed to keep the pressure in your system at the required level. Leaks generally occur in towards the end of production on pipework, connections, maintenance components as well as rapid-release couplings. As compressed air escapes, the gas molecules cause friction along the piping wall.

This friction in turn generates a noise in the ultrasonic frequency range. The **METPOINT® LKD** detects this noise and converts it into audible and visual signals. As it only picks up noise within the gas leak frequency range, the device allows for accurate detection even in noisy environments.

Even small leaks can make a big contribution to the costs for compressed air. In total, leakage rates of 30% are not uncommon. In times of rising energy prices, high sums of money therefore get wasted very quickly. The remedy here is the small and easy-to-use **METPOINT® LKD** Leak Detector. If it is utilized, then the leaks in the system can be located in a short time. Maintenance is therefore targeted accurately and possible at short notice.



It's clear who the hero is.



Successful plant operations are all about reliability and efficiency. That's why smart managers choose oil-free screw compressors from Kaeser.

With their *Built for a lifetime* engineering, our 2-stage oil-free rotary screw compressors deliver the best combination of efficiency and reliability.

- Flows from 192 to 1,774 cfm
- Pressures from 45 to 145 psig
- Designed for lower service costs and more uptime
- Fixed or variable speed models available
- Excellent specific performance (kW/100 cfm)
- Integrated refrigerated and heat-of-compression dryer options
- Advanced control and monitoring
- Heat recovery-ready

Learn more about how Kaeser's fresh take on oil-free design reduces downtime and increases your productivity. Visit us.kaeser.com/cabp.



Where innovation
meets reliability.

KAESER
COMPRESSORS®

Built for a lifetime.

Kaeser Compressors, Inc. • (866) 516-6888 • us.kaeser.com/cabp

The Kaeser logo is a registered trademark of Kaeser Kompressoren ©2021 Kaeser Compressors, Inc. All rights reserved. customer.us@kaeser.com